

## PRESSALIT®

Product	MATRIX CLIPVE II organomic wash basin with tan hole and everflow		
Item number	MATRIX CURVE II ergonomic wash basin with tap hole and overflow R2052000		
	VVS:636862300		
	NRF:6132513		
	RSK:7503001		
	EAN:5708590333861		
	HMI: 101015		
Colour	White		
Product description	MATRIX is a series of wash basins, most of them are designed by Pressalit.  MATRIX SMALL and CURVE wash basins fit onto PLUS, SELECT and VALUE was basin brackets, whereas MATRIX MEDIUM, ANGLE, ANGLE DEEP and SQUARE are tailor made to fit specific brackets.		
	MATRIX CURVE II ergonomic wash basin, 600 x 487 x 150 mm, with tap hole Ø36 mm and overflow.  Supplied with drain fitting. The concave front edge stabilises standing as well as seated users. The rounded edges are also comfortable to hold and rest against. The flat bottom leaves room for the legs underneath.  Material: Ceramic.  Suitable for wash basin brackets from the Pressalit PLUS, SELECT and VALUE ranges.		
Product capacity	150 kg.		
Materials	Ceramic		
Ergonomy	The concave front edge stabilises a standing as well as a seated user. The rounded shapes are nice to grip and lean against. The design of the corners leaves space and supports the elbows in the basin and t flat bottom leaves space for the legs of a seated user.		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.		
Cleaning	The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use corrosive cleaners. For surface disinfection, chlorine based agents can be used diluted according to specifications.		



# PRESSALIT.

Product Item number	MATRIX CURVE II ergonomic wash basin with tap hole and overflow R2052000
Declaration of conformity	Declaration of Performance Compliance criteria according to EN 14688:2015. 4.1 Load resistance: Pass. 4.2 Draining of water: Pass. 4.3 Resistance to temperature changes: Pass. 4.4 Resistance to chemicals and staining agents: Pass. 4.5 Surface stability / resistance to scratching: Pass. 4.6 Cleanability: Pass. 4.7 Protection against overflow: CL 15. 4.8 Durability: Pass.



## PRESSALIT®

Product	
Item number	

MATRIX CURVE II ergonomic wash basin with tap hole and overflow R2052000

#### Installation in different wall types

amorant man types	
Concrete >B25  V8602 - Mounting kit, 2 coach screws Ø10 x 100 - plugs SX12.  To be ordered separately	
Solid Brick >= Mz12  V8602 - Mounting kit, 2 coach screws Ø10 x 100 - plugs SX12.  To be ordered separately	
Solid Sand Lime Brick >= HIz12  V8602 - Mounting kit, 2 coach screws Ø10 x 100 - plugs SX12.  To be ordered separately	
Aerated Concrete P4  V8652 - Mounting kit, 2 coach screws Ø10 x 100 - plugs GB14.  To be ordered separately.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood  V8602 - Mounting kit, 2 countersunk screws Ø10 x 80, plugs SX12. NB! Plugs are not needed.  To be ordered separately.	



#### PRESSALIT®

Product Item number	MATRIX CURVE II ergonomic wash basin with tap hole and overflow R2052000	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood  Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	<u>^!</u>
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)  Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	<u>!</u>
	Drywall (2 x 12,5 mm) water-resistant	
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	<u>^!</u>

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com