

PRESSALIT.

Product Item number	MATRIX CURVE ergonomic wash basin with overflow R2050000	
Colour	VVS:636859100 NRF:6191675 EAN:5708590207957 HMI: 42540 NBS:N13:30,335 White	
Product description	MATRIX is a series of wash basins, most of them are designed by Pressalit. MATRIX SMALL and CURVE wash basins fit onto PLUS, SELECT and VALUE w basin brackets, whereas MATRIX MEDIUM, ANGLE, ANGLE DEEP and SQUAR are tailor made to fit specific brackets. MATRIX CURVE ergonomic wash basin, 600 x 490 x 190 mm, with tap hole Ø36 and overflow. Supplied with drain fitting. The concave front edge stabilises standing as well as seated users. The rounded edges are also comfortable to hold and rest against. If lat bottom leaves room for the legs underneath.	
	Material: Ceramic. Suitable for wash basin brackets from the Pressalit PLUS, SELECT and VALUE ranges.	
Product capacity	200 kg.	
Materials	Ceramic	
Ergonomy	The concave front edge stabilises a standing as well as a seated user. The rounded shapes are nice to grip and lean against. The design of the corners leaves space and supports the elbows in the basin and the flat bottom leaves space for the legs of a seated user.	
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.	



PRESSALIT.

Product Item number	MATRIX CURVE ergonomic wash basin with overflow R2050000
Cleaning	Wash basin For cleaning the wash basin, use hot water and a mild soapy cleaning agent. Make sure that the product is wiped down with a soft rag wrung out in clear water immediately after cleaning. For disinfecting the wash basin, the following agents can be used: Sodium hydroxide 5% Acetic acid solution 10% Ethanol solution 70% Sodium hypochlorite 5%, active chlorine Sodium chloride 170g/l, diluted to 50%. Make sure that the product is wiped down with a soft rag wrung out in clear water immediately after disinfection. NB! Do not use abrasive cleaning agents, as this will cause damage to the surface of the wash basin.



PRESSALIT.

Pro	duct

MATRIX CURVE ergonomic wash basin with overflow

Item number R2050000


Installation in different wall types


0.	1.0.1	(· · ·	. 0
3.		Δ.	€.
· ·	∇ a	Ø:	
	₹. ह	₽. ♥.	. 7
0.	Ŏ. D.	× 6.	
	.D: \(\text{\text{\$\sigma}}\)		.0

Concrete >B25

V8602 - Mounting kit, 2 coach screws Ø10 x 100 - plugs SX12.

To be ordered separately







Solid Brick >= Mz12

V8602 - Mounting kit, 2 coach screws Ø10 x 100 - plugs SX12.

To be ordered separately






Solid Sand Lime Brick >= Hlz12

V8602 - Mounting kit, 2 coach screws Ø10 x 100 - plugs SX12.

To be ordered separately







Aerated Concrete P4

V8652 - Mounting kit, 2 coach screws Ø10 x 100 - plugs GB14.

To be ordered separately.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8602 - Mounting kit, 2 countersunk screws Ø10 x 80, plugs SX12. NB! Plugs are not needed.

To be ordered separately.





PRESSALIT®

Product Item number	MATRIX CURVE ergonomic wash basin with overflow R2050000	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	<u>^</u>
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	<u>^</u>
	Drywall (2 x 12,5 mm) water-resistant Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	<u>^</u>

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com