

Pressalit Sway Uni 970
**Toilet seat with soft close, lift-off and antibacterial effect, incl. hinge in stainless steel


Incl. design emblems, brushed steel and brushed brass**

Features	Lift-off, Soft close
Item number	970001-D05999 EAN:5708590340609
	With its well-composed lines, SWAY Uni demonstrates how slimness and self-assurance can work together. Spoil yourself with a seat that is the perfect match for your stylish lifestyle.
Colour	Black (RAL 9005)
Description	PRESSALIT toilet seat with cover, model ”Pressalit Sway Uni”, art. no. 970 made of colour ingrained duroplast with soft close incl. D05 universal hinge with lift-off in stainless steel. - dismounting of seat/cover makes cleaning easier - centre distance: 92-170 mm - load - ring seat 240 kg - suitable for many universal toilets - 10 year guarantee









Design type	Sandwich
Designer	Pressalit
Design year	2016

Pressalit Sway Uni 970
**Toilet seat with soft close, lift-off and antibacterial effect, incl. hinge in stainless steel

Incl. design emblems, brushed steel and brushed brass**

Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde). UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing (< 0.01 mg/m³) to emit significantly below the permitted EU limit of 0.08 mg/m³. ANTIBACTERIAL: This toilet seat features an antibacterial additive with biocidal silver phosphate glass, which helps prevent bacterial growth. BUFFERS: EVA (copolymer made of ethylene and vinyl acetate). DAMPER KIT: Hydraulic damper with damper housing in stainless steel or thermoplastic, mounted with plastic parts in thermoplastic. MOUNT/HINGES: Stainless steel and thermoplastic.
Product capacity	Load - ring seat 240 kg
Weight	2,996 kg
Carton size	490x389x84 mm
Gross weight	3,605 kg
Crate size	502x401x428 mm
Weight per crate	18,025 kg
Qty per crate	5
Crates per pallet	12
Qty per pallet	60
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.

Pressalit Sway Uni 970
**Toilet seat with soft close, lift-off and antibacterial effect, incl. hinge in stainless steel

Incl. design emblems, brushed steel and brushed brass**

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.

In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model.

If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com