




PRESSALIT®

Product Item number	VALUE wash basin bracket, manually height adjustable with gas cylinder R1210000
Colour	VVS:654011300 NRF:6191663 EAN:5708590176710 HMI: 25575 NBS:N13:30,335 FDA:ILW/D142473 White
Product description	 VALUE wash basin bracket, wall-mounted. Manually height adjustable 315 mm, with gas-assisted lever control. Recommendation: flexible feed/waste system R2065/R2067 (UK market R2075/R2077) Incl. fixing bolts for wash basin. Incl. fixing bolts for brick wall. Plugs depend on wall type and must be ordered separately. VALUE wash basin bracket, wall-mounted. Manually height adjustable 315 mm, with gas-assisted lever control. Recommendation: flexible feed/waste system R2065/T2067. (UK market R2075/R2077) Incl. fixing bolts for wash basin. Materials: Rilsan-coated steel. Incl. fixing bolts for brick wall. Plugs depend on wall type and must be ordered separately.
Adjustability Adjustment height	Height adjustable 315 mm



PRESSALIT®

Product Item number	VALUE wash basin bracket, manually height adjustable with gas cylinder R1210000
Product capacity	Maximum load: 80 kg. Suitable for wash basins weighing no more than 22 kg. When the wash basin is loaded with 80 kg, each wall fastener will be carrying 20 kg. <i>Wash basin brackets need to be able to carry the weight of the wash basin, as well as support the weight of the person who is leaning against the wash basin or who is using the wash basin to rise from seated position.</i> <i>Neither wash basin nor wash basin bracket are intended to carry the full body weight of a person, and the test methods applicable to wash basin brackets reflect this: ISO 17966 prescribes a static test on the front edge of the wash basin at 75% of maximum user weight, i.e. when the maximum load on a wash basin bracket is given as 80 kg and the wash basin weighs 22 kg, it is – according to ISO 17966 – the equivalent of a user weighing 77 kg leaning on the front edge of the wash basin.</i>
Materials	Basic material: Steel Surface material: Rilsan
Features	Height adjustable 315 mm.
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.



Product	VALUE wash basin bracket, manually height adjustable with gas cylinder
Item number	R1210000
Cleaning	The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use corrosive or abrasive cleaners as it may result in the surface being damaged. For surface disinfection, chlorine-based disinfectants may be used according to the product specification and safety precautions for these products. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningsprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättssprit 70% NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.