PRESSALIT®

Product	PLUS wall track, 600 mm, right-grooved, for vertical mounting
Item number	R9876112
	VVS:615843106 NRF:7501074 EAN:5708590365978 HMI: 124192
Colour	Anthracite grey
Product description	Below a selection of products for fitting to the wall track. PLUS wall track, 600 mm, right-grooved, for vertical mounting. For height adjustable shower seats and folding seats. The cover plate hides bolts and wires and facilitates cleaning. Materials: Aluminium and polystyrene. Excl. mounting kit.
Adjustability	Fixed mounting
Materials	The wall track is primarily made of 10-micrometre anodized aluminium. The cover plate is made of polystyrene and the ends of the track are capped with ABS polymer.
Ergonomy	The vertical track enables height adjustment of the different products. If combined with the horizontal track, the available space in the bathroom can be utilized optimally. In environments with multiple users, the vertical track makes it possible to adjust the different products to individual user heights.
Features	The front cover plate conceals mounting bolts and any cables.
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.



Product	PLUS wall track, 600 mm, right-grooved, for vertical mounting
Item number	R9876112
Cleaning	

PLUS wall tracks
The product is to be cleaned with hot water or a mild soapy cleaning agent.
Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.

The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.

DISINFECTANTS:
Clinimax Difficil-S
Erisan OXY+
Sprit (husholdningssprit)
Suma Bac D10
Virkon
Rodalon Desinfektionsspray
Lysoformin Spezial
CaviCide
Sufanios Premium
Tvättsprit 70%

NON-DISINFECTANTS:
Suma Star free D1
Taski 100
Taski 200
Milizid Citro

The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.

DECALCIFICATION OF ALUMINUM PARTS:
Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts must be wiped over with a damp cloth wrung out in clear water.

PRESSALIT®

Product	PLUS wall track, 600 mm, right-grooved, for vertical mounting
Item number	R9876112

Installation in different wall types



Concrete >B25

V8612 - Mounting kit, 10 coach screws Ø8 x 70, plugs SX10.
To be ordered separately.





Solid Brick >= Mz12

V8612 - Mounting kit, 10 coach screws Ø8 x 70, plugs SX10.
To be ordered separately.





Solid Sand Lime Brick >= Hlz12

V8612 - Mounting kit, 10 coach screws Ø8 x 70, plugs SX10.
To be ordered separately.





Aerated Concrete P4

V8662 - Mounting kit, 10 countersunk bolts M8 x 35, plugs FTP M 8.
To be ordered separately.





Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8612 - Mounting kit, 10 coach screws Ø8 x 70, plugs SX10.
NB! Plugs are not needed.
To be ordered separately.



Product	PLUS wall track, 600 mm, right-grooved, for vertical mounting
Item number	R9876112



Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood

Wall fasteners (10 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.





Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)

Wall fasteners (10 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.





Drywall (2 x 12,5 mm) water-resistant

Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com