



PRESSALIT®

Pressalit Comfort D2 1050
Toilet seat with soft close, lift-off and antibacterial effect, incl.
hinge in stainless steel

Features

Lift-off, Soft close

Item number

1050111-DK3999
 VVS:615097111
 NRF:6190337
 RSK:7821935
 EAN:5708590370170

In addition to soft-close, the seat also have a lift-off function or is mounted with an attachment which locks the seat so that it cannot be removed. A seat which is suitable for private use and the project market. The seat is comfortable and stable and has a well thought out design. In addition, it is manufactured with an antibacterial effect, which prevents the growth of bacteria.






Colour

Black (RAL 9005)

Description

PRESSALIT toilet seat with cover, model "Pressalit Comfort D2", art. no. 1050 made of colour ingrained duroplast, with soft-close, incl. DK3 universal hinge with lift-off in stainless steel.
 - centre distance: 136-216 mm
 - load - ring seat 240 kg
 - 10 year guarantee



Design type

Wrap-over

Designer

Pressalit

Design year

2019



Pressalit Comfort D2 1050
Toilet seat with soft close, lift-off and antibacterial effect, incl.
hinge in stainless steel

Materials

TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing (< 0.01 mg/m³) to emit significantly below the permitted EU limit of 0.08 mg/m³.

ANTIBACTERIAL:

This toilet seat features an antibacterial additive with biocidal silver phosphate glass, which helps prevent bacterial growth.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT:

Hydraulic damper with damper housing in stainless steel or thermoplastic, mounted with plastic parts in thermoplastic.

MOUNT/HINGES:

Stainless steel and thermoplastic.

Product capacity

Load - ring seat 240 kg

Weight

2,748 kg

Carton size

488x388x72 mm

Gross weight

3,139 kg

Crate size

500x400x368 mm

Weight per crate

15,695 kg

Qty per crate

5

Crates per pallet

18

Qty per pallet

90

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



PRESSALIT®

Pressalit Comfort D2 1050

**Toilet seat with soft close, lift-off and antibacterial effect, incl.
hinge in stainless steel**

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

PRESSALIT®