

PRESSALIT.

Product Item number	PLUS handrail section 746 mm, incl. wall rosette RT322035 VVS:777569225		
	EAN:5708590146560	RT320 - A = 321	
	NBS:N13:436	RT321 - A = 608 RT322 - A = 746 RT323 - A = 1046	
Colour	Red (RAL 3003)		
Product description	PLUS hand rail tube, with wall rosette and connecting unit female joint. Length 746 mm, diameter 33 mm. Requires other hand rail elements for installation. Please enquire for special hand rail solutions. Please note that RT360 PLUS hand rail wall mounting with strap must always be installed at all joints of tubes or every 1200 mm. Excl. mounting kit. See Technical datasheet (pdf) for information on fixings suitable for various wall types.		
	PLUS hand rail tube, with wall roset Length 746 mm, diameter 33 mm. Requires other hand rail elements for Please enquire for special hand rail Please note that RT360 PLUS hand installed at all joints of tubes or ever Materials: Powder-coated aluminium Excl. mounting kit.	or installation. <i>solutions.</i> I rail wall mounting with strap must always be ry 1200 mm.	
Product capacity	Maximum load: With a span up to 1000 mm: 210 kg With a span up to 1300 mm: 150 kg.		
Materials	Basic material: Aluminium		
	Surface material: Polyester lacquer		
	Cover cap: Cycoloy plastic		
Ergonomy		ail to be held comfortably and firmly. The nakes it easy to take hold of the rail.	



PRESSALIT.

Product Item number	PLUS handrail section 746 mm, incl. wall rosette RT322035	
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.	
Cleaning	The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based or corrosive cleaners as it may result in the surface being damaged.	



PRESSALIT.

Product Item number	PLUS handrail section 746 mm, incl. wall rosette RT322035	
Installation in	different wall types	
	Concrete >B25 V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.	
	Solid Brick >= Mz12 V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.	
	Solid Sand Lime Brick >= Hlz12 V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.	
	Aerated Concrete P4 V8665 - Mounting kit, 4 bolts M5 x 50 - plugs FTP K 6. To be ordered separately.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8. NB! Plugs are not needed. To be ordered separately.	



PRESSALIT®

Product Item number	PLUS handrail section 746 mm, incl. wall rosette RT322035	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant	
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	!

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com