Product	MATRIX SMALL sink with overflow
Item number	R2020000

	VVS: 636857100
	NRF: 6132501
	RSK: 7502999
	EAN: 5708590325064
	HMI: 82610
	NBS: N13:30,335
Color	White

Product description

MATRIX is a series of sinks, most of them are designed by Pressalit.
MATRIX SMALL and CURVE sinks fit onto PLUS, SELECT and VALUE sink brackets, whereas MATRIX MEDIUM and ANGLE are tailor made to fit specific brackets.

MATRIX SMALL sink, 22.6" x 17.7" x 5.1", with two integrated grab handles in the front. With tap hole diameter 1.4" and overflow. Incl. drain fitting. The sink has raised edges, preventing water from running over the back or down the outer sides. Materials: Cultured marble with a high-polished, nonporous sanitary gel coating. Compatible with sink brackets from the Pressalit PLUS and SELECT ranges.

Product capacity	440 lbs.
Materials	Cultured marble with a high-polished, nonporous sanitary gel coating.
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.

| Product	MATRIX SMALL sink with overflow
Item number	R2020000

| **Cleaning**	For cleaning the wash basin, use hot water and a mild soapy cleaning agent. Make sure that the product is wiped down with a soft rag wrung out in clear water immediately after cleaning. For disinfecting the wash basin, the following agents can be used: Sodium hydroxide 5% Acetic acid solution 10% Ethanol solution 70% Sodium hypochlorite 5%, active chlorine Sodium chloride 170g/l, diluted to 50%. Make sure that the product is wiped down with a soft rag wrung out in clear water immediately after disinfection. **NB! Do not use abrasive cleaning agents, as this will cause damage to the surface of the wash basin.**

Product	MATRIX SMALL sink with overflow
Item number	R2020000

Mounting in different wall types

Concrete >B25

V8602 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs SX12.
To be ordered separately

Solid Brick >= Mz12

V8602 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs SX12.
To be ordered separately

Solid Sand Lime Brick >= Hlz12

V8602 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs SX12.
To be ordered separately

Aerated Concrete P4

V8652 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs GB14.
To be ordered separately.

Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8602 - Mounting kit, 2 countersunk bolts Ø10 x 80, plugs SX12. NB! Plugs are not needed.
To be ordered separately.

Product	MATRIX SMALL sink with overflow
Item number	R2020000

	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	⚠️
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	⚠️
	Drywall (2 x 12,5 mm) water-resistant Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	⚠️

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com