


Pressalit T 2 316
Standard toilet seat incl. hinge in stainless steel

Item number	316273-UN3999 EAN:5708590299426
	Pressalit T 2. Traditional Pressalit design with new values. The nylon hinge-links are invisibly mounted, again leaving the inner sides of seat and cover with an even, smooth surface. It not only looks good, it's also easy to clean.
Colour	Pergamon
Description	PRESSALIT toilet seat with cover, model "T 2", art. no. 316 made of colour ingrained duroplast with UN3 univertical hinge of stainless steel. - centre distance: 155 mm - load - ring seat 240 kg - with inlaid nylon hinge straps for easier cleaning - suitable for many universal toilets - 10 year guarantee









Design type	Sandwich
Designer	Pressalit
Design year	2001

Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde). UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing (< 0.01 mg/m³) to emit significantly below the permitted EU limit of 0.08 mg/m³. BUFFERS: EVA (copolymer made of ethylene and vinyl acetate). MOUNT/HINGES: Stainless steel and thermoplastic.

Pressalit T 2 316
Standard toilet seat incl. hinge in stainless steel

Product capacity	Load - ring seat 240 kg
Weight	2,9069 kg
Carton size	457x389x68 mm
Gross weight	3,3069 kg
Crate size	469x401x348 mm
Weight per crate	16,5345 kg
Qty per crate	5
Crates per pallet	18
Qty per pallet	90
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.
Warranty	Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price. Subject to changes in the product range, technical changes and printing errors.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com