



PRESSALIT®

Pressalit Plan 780

Toilet seat with soft close, lift-off and antibacterial effect, incl. combi hinge in stainless steel

Features

Lift-off, Soft close

Item number

780000-D98999
NRF:6190226
EAN:5708590319728

Pressalit Plan stands for perfect fit and has a stunning square design with soft close and lift-off. Specially designed for Keramag Renova No.1 Plan.




Colour

White

Description

PRESSALIT toilet seat with cover, model "Pressalit Plan", art. no. 780 made of colour ingrained duroplast with D98 fixed hinge of stainless steel and plastic.

- centre distance: 155 mm
- load - ring seat 240 kg
- suitable for Keramag Renova Nr. 1 Plan
- 10 year guarantee



Design type

Wrap-over

Designer

Pressalit

Design year

2012



Pressalit Plan 780

Toilet seat with soft close, lift-off and antibacterial effect, incl. combi hinge in stainless steel

Materials

TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing ($< 0.01 \text{ mg/m}^3$) to emit significantly below the permitted EU limit of 0.08 mg/m^3 .

ANTIBACTERIAL:

This toilet seat features an antibacterial additive with biocidal silver phosphate glass, which helps prevent bacterial growth.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT:

Hydraulic damper with damper housing in stainless steel or thermoplastic, mounted with plastic parts in thermoplastic.

MOUNT/HINGES:

Stainless steel and thermoplastic.

Product capacity

Load - ring seat 180 kg

Weight

2,591 kg

Carton size

488x388x72 mm

Gross weight

2,951 kg

Crate size

500x400x368 mm

Weight per crate

14,755 kg

Qty per crate

5

Crates per pallet

18

Qty per pallet

90

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



PRESSALIT®

Pressalit Plan 780

**Toilet seat with soft close, lift-off and antibacterial effect, incl.
combi hinge in stainless steel**

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

PRESSALIT®