



PRESSALIT®

Pressalit Objecta Pro without cover 989
Standard toilet seat with antibacterial effect, without cover, incl.
hinge in stainless steel

Item number

989011-DH4999
 EAN:5708590344744




Pressalit Objecta Pro - without cover. A well-designed seat for the project market with an antibacterial effect. Beautiful and slim design that fits a wide range of bowls.

Colour

White

Description

PRESSALIT toilet seat without cover, model "Objecta Pro", art.no. 989 made of colour ingrained duroplast, incl. DH4 combi hinge, univertical, in stainless steel.
 - centre distance: 155 mm
 - load - ring seat 240 kg
 - 10 year guarantee



Design type

Sandwich

Designer

Pressalit

Design year

2016



Pressalit Objecta Pro without cover 989
Standard toilet seat with antibacterial effect, without cover, incl.
hinge in stainless steel

Materials

TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

ANTIBACTERIAL:

This toilet seat features an antibacterial additive with biocidal silver chloride, which helps prevent bacterial growth.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.

Product capacity

Load - ring seat 240 kg

Weight

1,304 kg

Carton size

490x389x84 mm

Gross weight

1,644 kg

Crate size

479x399x458 mm

Weight per crate

8,22 kg

Qty per crate

5

Crates per pallet

8

Qty per pallet

40

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



PRESSALIT®

Pressalit Objecta Pro without cover 989
Standard toilet seat with antibacterial effect, without cover, incl.
hinge in stainless steel

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com
