

## PRESSALIT.

Product	Mattress
Item number	R8481378
	VVS:777540928 EAN:5708590376592 HMI: 138102
Colour	Navy blue
Product description	Mattress for change table, 680 x 1100 mm.  The mattress is easily removed, which offers flexibility of use and ensures optimum opportunity for effective cleaning over and under the mattress.  The mattress scan be turned over and is made from a pleasant hypoallergenic material with a surface that is easy to wipe down and keep clean.
	Mattress for change table, 680 x 1100 mm.  The mattress is easily removed, which offers flexibility of use and ensures optimum opportunity for effective cleaning over and under the mattress.  The mattress scan be turned over and is made from a pleasant hypoallergenic material with a surface that is easy to wipe down and keep clean.
Materials	The mattress cover is manufactured from 100% polyester with polyurethane, approved in accordance with Oeko-Tex 100, Class I. It is fire retardant and impermeable to dust mites. The foam filling is flexible polyester-based polyurethane foam, which is also fire retardant and approved in accordance with Oeko-tex 100, Class I. The mattress cover is manufactured from 100% polyester with polyurethane, approved in accordance with Oeko-Tex 100, Class I. It is fire retardant and impermeable to dust mites. The foam filling is flexible polyester-based polyurethane foam, which is also fire retardant and approved in accordance with Oeko-tex 100, Class I.



## PRESSALIT®

Product	Mattress
Item number	R8481378
Cleaning	CT and MCT mattresses The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.  The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.  DISINFECTANTS: Sprit (husholdningssprit) Tvättsprit 70% Safe Zone Plus Selgiene Extreme Accel PREVention Wipes Lingettes  The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com

PRESSALIT.