

Product	SCT 3000 shower change table, fixed height		
Item number	R8435318301		
	VVS:777543193		
	EAN:5708590374048		
	HMI: 130171		
	FDA: INT/D124320		
Color	Graphite gray (RAL 7024)		
Product description	Pressalit offers a variety of mobile and wall-hung, height-adjustable and fixed height shower and changing tables of high quality. They are designed to provide a stable platform for showering and changing adults and children with reduced mobility. These tables can be used in schools, institutions, hospitals and private homes and are all designed to be durable, comfortable and easy to clean. The design and flexibility of the tables ensures optimal working conditions for the carer as well as a high level of comfort and safety for the user. The SCT 3000 series has a stylish and award-winning design focused on comfort are ease of use.		
	SCT 3000 shower change table, fixed height. Foldable. Incl. safety rail, flexible hose (Ø1.26") and water collection tray with integrated outlet. Surface length 70.9", outer measurements 40.6" x 75.2". Excl. mounting kit.		
Adjustability	Fixed mounting		
Product capacity	Maximum user weight (MUM): 441 lbs. Maximum load (SWL): 463 lbs. When the table is loaded with 441 lbs, each mounting bolt supports 132 lbs. This product has been tested statically with a load of 694 lbs, as the ISO 17966 standard requires testing with a safety factor 1.5.		
Materials	Powder-lacquered stainless steel, aluminium and plastics (PVC, Polystyrene). Pads i polyurethane foam, are tested according to the DIN EN 1021-1 standard (flame resistance).		



Product	SCT 3000 shower change table, fixed height	
Item number	R8435318301	
Ergonomy	 The ergonomically designed safety rails have a practical lower central section, which provides better access and work environment for the carer while transferrin showering, drying, changing and dressing the user. One hand operated safety rails allows the carer to maintain eye contact as well a physical contact with the user during the whole process. Easy to clean, smooth contact surfaces which do not collect dirt and bacteria. 	
Features	 A water collection tray with integrated water outlet prevents water from splashing caregiver or the floor. The flexible hose (Ø1.26") attached to the center mounted outlet of the water collection tray, can be connected to either an outlet in the floor con the wall. Adjustable neck support which can be moved to either end of the 51.2" changing tables. The slightly curved shape makes the table comfortable and safe to lie on •The integrated pneumatic cylinders enable the table to be folded out of the way when n in use to maximize floor space. 	
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. NOTICE If the product is placed in an atmosphere heavy in salt or chloride, the warranty will be reduced from the normal 3 years to 1 year. Salt and chloride have a corrosive effect on the products components and will cause a decrease in the life expectancy of the product.	



Product Item number	SCT 3000 shower change table, fixed height R8435318301
Cleaning	This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% Accel PREVention Wipes Lingettes

NON-DISINFECTANTS:

OxiGenesis from ENVIROX

Suma Star free D1

Taski 100 Taski 200 Milizid Citro

The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.

DECALCIFICATION OF ALUMINUM PARTS:

Pressalit recommends that water deposits (Calcium, lime etc.) be removed from wall tracks and other aluminum parts using a solution of three parts of 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts should be wiped over with a damp cloth wrung out in plain water.



Product

SCT 3000 shower change table, fixed height

Item number

R8435318301


Mounting in different wall types


g.	v\.;\.;\.	7 0
.کا.	.∇ . ° . <	2.0
·.·		√√.
	D : C	D

Concrete >B25

V8613 - Mounting kit, 8 lag bolts Ø10 x 70, plugs SX12, with grey covers.

To be ordered separately.







Solid Brick >= Mz12

V8613 - Mounting kit, 8 lag bolts \emptyset 10 x 70, plugs SX12, with grey covers.

To be ordered separately.






Solid Sand Lime Brick >= Hlz12

V8613 - Mounting kit, 8 lag bolts Ø10 x 70, plugs SX12, with grey covers.

To be ordered separately.






Aerated Concrete P4

V8663 - Mounting kit, 8 lag bolts \emptyset 10 x 70, plugs GB14, with grey covers.

To be ordered separately.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8613 - Mounting kit, 8 lag bolts Ø10 x 70, plugs SX12, with grey covers. NB! Plugs are not needed.

To be ordered separately.





PRESSALIT®

Product Item number	SCT 3000 shower change table, fixed height R8435318301	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (10 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Wall fasteners (10 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant	
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	!

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com