
PRESSALIT®

Product	Changing table, 800 x 900 mm, electrically height adjustable, foldable
Item number	R8721000
Colour	VVS:777630110 NRF:7501913 RSK:8565146 EAN:5708590286211 HMI: 48864 White



Product description

Pressalit offers a wide range of daycare changing tables, both free-standing and wall-hung, in several sizes and models. The wall-hung tables are also available in versions where the worktop folds away, which are suitable for rooms with limited space.
Of particular use to daycare facilities and kindergartens are the low start wall-hung changing tables, which can be lowered to a height that allows children to climb onto the worktop themselves.
All types of daycare changing tables are available in versions with sanitary appliances and a choice of taps, with or without pull-out shower heads.

Wallhung, foldable changing table, 800 x 900 mm.
With electric motor and transformer, height adjustable from 650 mm - 1000 mm, with wired hand control.
Materials: Molded worktop in ABS plastics, synthetic acrylic and powder-lacquered steel.
Excl. mounting kit.

Adjustability	Height adjustable
Adjustment height	350 mm
Product capacity	Max load: 75 kg.
Speed upwards	Speed up mm: 14 mm/s Speed down mm: 14 mm/s
Noise level	48 dB
Materials	Lifting unit: Powder-laquered steel. Worktop: ABS with acrylic.
Ergonomy	The smooth height adjustment ensures that it is always possible to set the table at an ergonomically correct height.











PRESSALIT®

Product	Changing table, 800 x 900 mm, electrically height adjustable, foldable
Item number	R8721000
Features	Easy-to-clean surfaces ensure optimum hygiene. The integrated gas cylinder enables the table to be folded easely against the wall when not in use to maximise floor space.
Mains connection (V)	230
Actuator (motor)	LA31 Deskline (Linak), 1500N, IPX1
Control box	CBD6 (Linak), IP20
Wired remote control	HB30 (Linak), IPX4
Power consumption (maximum load)	Power consumption by maximum load, watt: 96 W Power consumption by standby: 0,1 W
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.


Product	Changing table, 800 x 900 mm, electrically height adjustable, foldable
Item number	R8721000
Cleaning	The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.
WEEE	Please enquire of your local Pressalit subsidiary or distributor (in countries where there is no subsidiary) that will arrange for recycling of electronic waste in accordance with the WEEE directive.

Product	Changing table, 800 x 900 mm, electrically height adjustable, foldable
Item number	R8721000

Installation in different wall types


	**Concrete >B25** V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
	**Solid Brick >= Mz12** V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
	**Solid Sand Lime Brick >= Hlz12** V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
	**Aerated Concrete P4** V8658 - Mounting kit, 6 coach screws Ø10 x 70 - plugs GB14. To be ordered separately.	
	**Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood** V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.	


Product	Changing table, 800 x 900 mm, electrically height adjustable, foldable
Item number	R8721000



Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood


Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)

Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.





Drywall (2 x 12,5 mm) water-resistant

Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.



Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com