

PRESSALIT.

Product	SCT 1000 shower change table , electrically height adjustable			
Item number	R8583118000			
	VVS:777543680			
	EAN:5708590377643			
	HMI: 140133			
Colour	White	750		
Product description	Pressalit offers a variety of mobile and wall-hung, height-adjustable and shower and changing tables of high quality. They are designed to provide platform for showering and changing adults and children with reduced material theorems. These tables can be used in schools, institutions, hospitals and private hare all designed to be durable, comfortable and easy to clean. The design and flexibility of the tables ensures optimal working condition carer as well as a high level of comfort and safety for the user.			
	SCT 1000 shower change table 1000, powered, height adjustable 400 mm; from 4 mm - 880 mm, with wired hand control Foldable. Incl. safety rail. Outer measurements 760 mm x 1800 mm. Excl. mounting kit.			
Adjustability	Height adjustable			
Adjustment height	400 mm			
Product capacity	Maximum user weight (MUM): 200 kg. Safe working load (SWL): 200 kg. When the table is loaded with 200 kg, each mounting bolt supports 27 kg. This product has been tested statically with a load of 500 kg as the IEC 60601-1 standard requires testing with safety factor 2.5.			
Speed upwards	Speed up mm: 11 mm/s Speed down mm: 9 mm/s			
Noise level	50 dB			
Materials		d durable PVC canvas which is phthalate free.		



PRESSALIT.

SCT 1000 shower change table , electrically height adjustable	
R8583118000	
Carers can easily set the height of the table, enabling them to obtain the correct working position. This ensures safe showering and changing for the user as well as minimizing the risk of back injury for the carer.	
Electric with wired hand control – the red buttons clearly indicate "Up" and "Down". The wired hand control comes with a holder for fitting to the wall. The integrated gas cylinders enable the bench to be folded out of the way when not n use to maximise floor space in front of the unit. Splash curtain (optional) for the nursing bench protects the carer against splashing.	
230	
LA40 Careline (Linak), 4000 N, IPX6	
CA63 Careline (Linak), IPX6	
HB30 (Linak), IP66	
Power consumption by maximum load, watt: 420 W Power consumption by standby: 0,5 W	
Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. NOTICE If the product is placed in an atmosphere heavy in salt or chloride, the warranty will be reduced from the normal 3 years to 1 year. Salt and chloride have a corrosive effect on the products components and will cause a decrease in the life expectancy of the product.	



PRESSALIT.

Product Item number	SCT 1000 shower change table , electrically height adjustable R8583118000	
Cleaning		
Oleaning	SCT 1000 & 2000	
	The product is to be cleaned with hot water or a mild soapy cleaning agent.	
	Do not use chlorine based, corrosive or abrasive cleaners as it may result in the	
	surface being damaged.	
	The following cleaning agents have been tested by Pressalit and may be used, as	
	long as they are diluted according to the instructions on the container.	
	DISINFECTANTS:	
	Clinimax Difficil-S	
	Erisan OXY+	
	Sprit (husholdningssprit)	
	Suma Bac D10	
	Virkon	
	Rodalon Desinfektionsspray	
	Lysoformin Spezial	
	CaviCide	
	Sufanios Premium	
	Tvättsprit 70%	
	Accel PREVention Wipes Lingettes	
	OxiGenesis from ENVIROX	
	NON-DISINFECTANTS:	
	Suma Star free D1	
	Taski 100	
	Taski 200	
	Milizid Citro	
	The product must be wiped down with a soft rag wrung out in clear water immedia	
	after cleaning, as some materials may otherwise be discolored and stained, and t surface coating may deteriorate.	



PRESSALIT®

Prod	luct
ltom	numb

SCT 1000 shower change table , electrically height adjustable $\,$

R8583118000

Installation in different wall types

7 1	
Concrete >B25 V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
Solid Brick >= Mz12 V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
Solid Sand Lime Brick >= Hlz12 V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
Aerated Concrete P4 V8658 - Mounting kit, 6 coach screws Ø10 x 70 - plugs GB14. To be ordered separately.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.	



PRESSALIT®

Product Item number	SCT 1000 shower change table , electrically height adjustable R8583118000		
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.		
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.		
	Drywall (2 x 12,5 mm) water-resistant		
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	<u>^</u>	

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com