

### PRESSALIT®

Product Item number	Changing table, 800 x 1400 mm, electrically height adjustable, foldable R8672000			
Colour	VVS:777636120 NRF:7501978 EAN:5708590338392 HMI: 48573 White			
Product description	Pressalit offers a wide range of daycare changing tables, both free-standing and wall-hung, in several sizes and models. The wall-hung tables are also available in versions where the worktop folds away, which are suitable for rooms with limited space. Of particular use to daycare facilities and kindergartens are the low start wall-hung changing tables, which can be lowered to a height that allows children to climb onto the worktop themselves.  All types of daycare changing tables are available in versions with sanitary appliances and a choice of taps, with or without pull-out shower heads.  Low start, wallhung, foldable changing table, 800 x 1400 mm.  With electric motor and transformer, height adjustable from 300 mm - 1000 mm, with wired hand control.			
	Materials: Molded worktop in ABS plastics, synthetic acrylic and powder-lacquered steel.  Excl. mounting kit.			
Adjustability	Height adjustable			
Adjustment height	700 mm			
Product capacity	Max load: 75 kg.			
Speed upwards	Speed up mm: 38 mm/s Speed down mm: 38 mm/s			
Noise level	48 dB			
Materials	Lifting unit: Powder-laquered steel. Worktop: ABS with acrylic.			



# PRESSALIT.

Product	Changing table, 800 x 1400 mm, electrically height adjustable, foldable		
Item number	R8672000		
Ergonomy	The smooth height adjustment ensures that it is always possible to set the table at ergonomically correct height.  The table descends to a very low position, which offers the advantage that toddler can easily climb up and down themselves. Thereby unnecessary lifting is avoided.		
Features	Easy-to-clean surfaces ensure optimum hygiene.  The integrated gas cylinder enables the table to be folded easely against the wall when not in use to maximise floor space.  Integrated safety system prevents entrapment.		
Mains connection (V)	230		
Actuator (motor)	LA31 Deskline (Linak), 2500N, IPX1		
Control box	CBD6 (Linak), IP20		
Wired remote control	HB30 (Linak), IPX4		
Power consumption (maximum load)	Power consumption by maximum load, watt: 96 W Power consumption by standby: 0,1 W		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.		



## PRESSALIT.

Product	Changing table, 800 x 1400 mm, electrically height adjustable, foldable
Item number	R8672000
Cleaning	
-	Daycare changing tables The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.
	DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70%
	NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro
	The product must be wiped down with a soft rag wrung out in clear water immediate after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.
Declaration of conformity	CE UK MASK-ROHS This product complies with the relevant requirements of: - Council Directive 2006/42/EC on machinery - Council Directive 2011/65/EC on RoHS. For the UK: - The Supply of Machinery (Safety) Regulations 2008 - Restriction of the Use of Certain Hazardous Substances in Electrical and Electron Equipment Regulations 2012



#### PRESSALIT®

Product					
Item	numbe				

Changing table,  $800 \times 1400 \text{ mm}$ , electrically height adjustable, foldable R8672000

#### Installation in different wall types

amorant wan types	
Concrete >B25  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Solid Brick >= Mz12  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Solid Sand Lime Brick >= Hlz12  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Aerated Concrete P4  V8658 - Mounting kit, 6 coach screws Ø10 x 70 - plugs GB14.  To be ordered separately.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. NB! Plugs are not needed.  To be ordered separately.	



### PRESSALIT®

Product Item num	ber	Changing table, 800 x 1400 mm, electrically height adjustable, foldable R8672000				
		Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood  Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.		<b>○ 9</b>		
		Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)  Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.				
		Drywall (2 x 12,5 mm) water-resistant  Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	_	<u>?</u>		

pressalit.com