



Pressalit Objecta / Projecta / Projecta Plus without cover 53
Standard toilet seat with antibacterial effect, without cover, incl. hinge in stainless steel

Item number	53111-BA1999 EAN:5708590321585
	Pressalit Objecta/Projecta/Projecta Plus - without cover. Project seats are universal seats and contains an antibacterial effect, which prevents the growth of bacteria 24/7. Particularly suited to building projects.
Colour	Black (RAL 9005)
Description	PRESSALIT toilet seat without cover, model "Objecta", art.no. 53 made of colour ingrained duroplast, incl. BA1 fixed hinge in stainless steel. - centre distance: 155 mm - load - ring seat 240 kg - 10 year guarantee









Designer	Pressalit
Design year	1982
Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde). UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing (< 0.01 mg/m³) to emit significantly below the permitted EU limit of 0.08 mg/m³. ANTIBACTERIAL: This toilet seat features an antibacterial additive with biocidal silver phosphate glass, which helps prevent bacterial growth. BUFFERS: EVA (copolymer made of ethylene and vinyl acetate). MOUNT/HINGES: Stainless steel and thermoplastic.
Product capacity	Load - ring seat 240 kg

Pressalit Objecta / Projecta / Projecta Plus without cover 53
Standard toilet seat with antibacterial effect, without cover, incl. hinge in stainless steel

Weight	1,169 kg
Carton size	457x389x68 mm
Gross weight	1,569 kg
Crate size	469x401x348 mm
Weight per crate	7,845 kg
Qty per crate	5
Crates per pallet	18
Qty per pallet	90
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.
Warranty	Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price. Subject to changes in the product range, technical changes and printing errors.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com