



PRESSALIT®

Pressalit Objecta D / Projecta D 172
Standard toilet seat with antibacterial effect, incl. institutional
hinge in stainless steel

Item number

172111-D28999
 EAN:5708590336220

Pressalit Objecta D/Projecta D is a simple and practical toilet seat specially developed for the sanitary lines Duravit Starck 2, Starck 3 (only Objecta D), Happy D and others. Contains an antibacterial effect, which prevents the growth of bacteria 24/7. Particularly suited to building projects.






Colour

Black (RAL 9005)

Description

PRESSALIT toilet seat with cover, model "Projecta D", art.no. 172 made of colour ingrained duroplast, with D28 fixed institutional hinge in stainless steel.
 - centre distance: 150/170 mm
 - load - ring seat 240 kg
 - 10 year guarantee



Design type

Sandwich

Designer

Pressalit

Design year

2002



Pressalit Objecta D / Projecta D 172
Standard toilet seat with antibacterial effect, incl. institutional
hinge in stainless steel

Materials

TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing (< 0.01 mg/m³) to emit significantly below the permitted EU limit of 0.08 mg/m³.

ANTIBACTERIAL:

This toilet seat features an antibacterial additive with biocidal silver phosphate glass, which helps prevent bacterial growth.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

MOUNT/HINGES:

Stainless steel and thermoplastic.

Product capacity

Load - ring seat 240 kg

Weight

3,425 kg

Carton size

457x389x68 mm

Gross weight

3,825 kg

Crate size

469x401x348 mm

Weight per crate

19,125 kg

Qty per crate

5

Crates per pallet

18

Qty per pallet

90

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



PRESSALIT®

Pressalit Objecta D / Projecta D 172
Standard toilet seat with antibacterial effect, incl. institutional
hinge in stainless steel

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com
