

PRESSALIT.

Pressalit Objecta D Pro without cover 997 Standard toilet seat with antibacterial effect, without cover, incl. hinge in stainless steel

ltem number	997011-DF7999 EAN:5708590345475 Pressalit Objecta D Pro - without cover. D-shaped seat, which is well suited to the project market, with an antibacterial effect. Harmonious design and ultimate strength.
Colour	White
Description	PRESSALIT toilet seat without cover, model "Objecta D Pro", art.no. 997 made of colour ingrained duroplast, incl. DF7 fixed hinge in stainless steel. - centre distance: 155 mm - load - ring seat 240 kg - 10 year guarantee
	434 434 434 226 275 47171 A7202 A7156 A7023 A7050 *60 mm
Design type	Sandwich
Designer	Pressalit
Design year	2016



Pressalit Objecta D Pro without cover 997 Standard toilet seat with antibacterial effect, without cover, incl. hinge in stainless steel	
Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.
	ANTIBACTERIAL: This toilet seat features an antibacterial additive with biocidal silver chloride, which helps prevent bacterial growth.
	BUFFERS: EVA (copolymer made of ethylene and vinyl acetate).
	DAMPER KIT (only relevant for toilet seats with soft close): Hydraulic damper with stainless steel damper casing and thermoplastic parts.
Product capacity	MOUNT/HINGES: Stainless steel model W. no. 1.4301/M and thermoplastic. Load - ring seat 240 kg
Weight	1,323 kg
Carton size	490x389x84 mm
Gross weight	1,663 kg
Crate size	479x399x458 mm
Weight per crate	8,315 kg
Qty per crate	5
Crates per pallet	8
Qty per pallet	40
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



Pressalit Objecta D Pro without cover 997 Standard toilet seat with antibacterial effect, without cover, incl. hinge in stainless steel

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

