



PRESSALIT®

Pressalit 2000 124 Standard toilet seat incl. institutional hinge in stainless steel

Item number	124000-BV7999 EAN:5708590269023
Colour	White
Description	PRESSALIT toilet seat with cover, model "2000", art. no. 124 made of colour ingrained duroplast with BV7 institutional hinge, universal of stainless steel. - centre distance: 95 - 190 mm - load - ring seat 240 kg - suitable for many universal toilets - 10 year guarantee
Design type	Sandwich
Designer	Pressalit
Design year	1991
Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde). UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing ($< 0.01 \text{ mg/m}^3$) to emit significantly below the permitted EU limit of 0.08 mg/m^3. BUFFERS: EVA (copolymer made of ethylene and vinyl acetate). MOUNT/HINGES: Stainless steel and thermoplastic.
Product capacity	Load - ring seat 240 kg
Weight	2,657 kg




124000-BV7999
EAN:5708590269023

The cover on the Pressalit 2000 is smaller than the ring seat, giving it a light and elegant design.

White

PRESSALIT toilet seat with cover, model "2000", art. no. 124 made of colour ingrained duroplast with BV7 institutional hinge, universal of stainless steel.

- centre distance: 95 - 190 mm
- load - ring seat 240 kg
- suitable for many universal toilets
- 10 year guarantee





PRESSALIT®

Pressalit 2000 124
Standard toilet seat incl. institutional hinge in stainless steel

Carton size	457x389x68 mm
Gross weight	2,957 kg
Crate size	469x401x348 mm
Weight per crate	14,785 kg
Qty per crate	5
Crates per pallet	18
Qty per pallet	90
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.
Warranty	Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price. Subject to changes in the product range, technical changes and printing errors.

pressalit.com
