



PRESSALIT®

Pressalit Spira V 1136
Toilet seat with soft close, lift-off and antibacterial effect, incl.
hinge in stainless steel

Features

Lift-off, Soft close

Item number

1136111-DM8999
 VVS:615072111
 NRF:1476350
 RSK:7824078
 EAN:5708590394619

Pressalit Spira V is an elegant and functional toilet seat designed for Ifö Spira toilets. With its sleek and modern appearance, it fits perfectly into style-conscious homes. Spira V combines innovative technology with comfort and durability, ensuring a stable and silent experience every time. Designed and produced in Denmark – a quality choice for the modern bathroom.






Colour

Black (RAL 9005)

Description

PRESSALIT toilet seat with cover, model "Pressalit Spira V", art. no. 1136 made of colour ingrained duroplast with antibacterial effect, with built-in soft close function, incl. DM8 hinge with lift-off in stainless steel.

- dismounting of seat/cover makes cleaning easier
- centre distance: 155 mm
- load - ring seat 240 kg
- 10 year guarantee



Design type

Sandwich

Designer

Pressalit

Design year

2024



Pressalit Spira V 1136
Toilet seat with soft close, lift-off and antibacterial effect, incl.
hinge in stainless steel

Materials

TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing (< 0.01 mg/m³) to emit significantly below the permitted EU limit of 0.08 mg/m³.

ANTIBACTERIAL:

This toilet seat features an antibacterial additive with biocidal silver phosphate glass, which helps prevent bacterial growth.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel and thermoplastic.

Product capacity

Load - ring seat 240 kg

Weight

2,401 kg

Carton size

457x389x68 mm

Gross weight

2,825 kg

Crate size

469x401x348 mm

Weight per crate

14,125 kg

Qty per crate

5

Crates per pallet

12

Qty per pallet

60

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



PRESSALIT®

Pressalit Spira V 1136

**Toilet seat with soft close, lift-off and antibacterial effect, incl.
hinge in stainless steel**

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com
