



PRESSALIT®

Pressalit Projecta Solid Pro without cover 1003

**Toilet seat with soft close and antibacterial effect, without cover,
incl. Solid Pro hinge**

Features

Soft close

Item number

1003011-DG4925

EAN:5708590344676

Pressalit Projecta Solid Pro - without cover. A design-conscious choice for the project market. With an antibacterial effect and strong fittings that ensure optimum stability - even during sideways transfer. The market's first institution seat with integrated soft closing function.






Colour

White

Description

PRESSALIT toilet seat without cover, model "Projecta Solid Pro", art.no. 1003 made of colour ingrained duroplast, incl. DG4 combi hinge, universal.

- built-in soft close function
- centre distance: 145-210 mm
- load - ring seat 240 kg
- 10 year guarantee



Design type

Sandwich

Designer

Pressalit

Design year

2016



Pressalit Projecta Solid Pro without cover 1003

**Toilet seat with soft close and antibacterial effect, without cover,
incl. Solid Pro hinge**

Materials**TOILET SEAT:**

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing ($< 0.01 \text{ mg/m}^3$) to emit significantly below the permitted EU limit of 0.08 mg/m^3 .

ANTIBACTERIAL:

This toilet seat features an antibacterial additive with biocidal silver phosphate glass, which helps prevent bacterial growth.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT:

Hydraulic damper with damper housing in stainless steel or thermoplastic, mounted with plastic parts in thermoplastic.

MOUNT/HINGES:

Stainless steel. Thermoplastic semi-crystalline polyamides with partially aromatic content. Aluminium profile EN AW-6063-TS.

Product capacity

Load - ring seat 240 kg

Weight

1,466 kg

Carton size

490x389x84 mm

Gross weight

1,806 kg

Crate size

517x399x456 mm

Weight per crate

9,03 kg

Qty per crate

5

Crates per pallet

8

Qty per pallet

40

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



PRESSALIT®

Pressalit Projecta Solid Pro without cover 1003**Toilet seat with soft close and antibacterial effect, without cover,
incl. Solid Pro hinge**

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

PRESSALIT®