
PRESSALIT®

Product	SCT 2000 shower change table, coated mesh cover, electrically height adjustable with wall-mounted safety stop and backup battery
Item number	R8581218000D
	EAN:5708590400303
Colour	White



Product description

Pressalit offers a variety of mobile and wall-hung, height-adjustable and fixed height shower and changing tables of high quality. They are designed to provide a stable platform for showering and changing adults and children with reduced mobility. These tables can be used in schools, institutions, hospitals and private homes and are all designed to be durable, comfortable and easy to clean.
The design and flexibility of the tables ensures optimal working conditions for the carer as well as a high level of comfort and safety for the user.

SCT 2000 shower change table with wall-mounted safety stop and backup battery, powered, height adjustable 700 mm; from 300 mm -1000 mm, with wired hand control Foldable. Incl. safety rail and water collection tray with integrated outlet.
Outer measurements 910 mm x 1800 mm.
Excl. mounting kit.

Adjustability	Height adjustable
Adjustment height	700 mm
Product capacity	Maximum user weight (MUM): 200 kg. Safe working load (SWL): 200 kg. When the table is loaded with 200 kg, each mounting bolt supports 26 kg *This product has been tested statically with a load of 500 kg as the IEC 60601-1 standard requires testing with safety factor 2.5.*
Speed upwards	Speed up mm: 19 mm/s Speed down mm: 21 mm/s
Noise level	50 dB
Materials	Construction in powder-laquered stainless steel, mesh cover in PVC-coated polyester (for extra durability), water collection tray in PVC-U and carriage housing in polystyrene.











PRESSALIT®






Product	SCT 2000 shower change table, coated mesh cover, electrically height adjustable with wall-mounted safety stop and backup battery
Item number	R8581218000D
Ergonomy	The 2000 series shower and changing tables has a low start position, to make transfers to the bench easier. The washable, perforated mesh cover lets the water pass through to the water collection tray underneath. The flexibility of the shower and changing table provides for optimal working conditions for the carer as well as a high level of comfort and safety for the user.
Features	• Wall-mounted safety stop The wall mounted safety stop is an optional breaker system which shuts down the operation of the changing table when activated. When the turn knob is deactivated, you may operate the table as normal. The safety stop can be mounted externally and does not require changes in the wall structure. • Backup battery The backup battery is an optional factory mounted feature which allows for continued operation in the event of a power failure. The backup battery allows for app. 15 cycles (up/down) depending on the load. The battery automatically charges when the changing table is connected to power. • A water collection tray with integrated water outlet prevents water from splashing on carers or the floor. The flexible hose attached to the centre mounted outlet of the water collection tray, can be connected to either an outlet in the floor or on the wall. • The integrated gas cylinders enable the table to be folded out of the way when not in use to maximise floor space in front of the unit. • Electric with wired hand control – the red buttons clearly indicate “Up” and “Down”. The wired hand control comes with a holder for fitting to the wall. • The stretcher of the table is very easy to clean, and the stretcher cover can be unzipped for washing or easy replacement.
Mains connection (V)	230
Actuator (motor)	LA40 Careline (Linak), 4000 N, IPX6
Control box	CA63 Careline, (Linak), IPX6
Wired remote control	HB30 (Linak), IP66
Power consumption (maximum load)	Power consumption by maximum load, watt: 420 W Power consumption by standby: 2,5 W

Product	SCT 2000 shower change table, coated mesh cover, electrically height adjustable with wall-mounted safety stop and backup battery
Item number	R8581218000D
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. NOTICE If the product is placed in an atmosphere heavy in salt or chloride, the warranty will be reduced from the normal 3 years to 1 year. Salt and chloride have a corrosive effect on the products components and will cause a decrease in the life expectancy of the product.
Cleaning	The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% Accel PREVention Wipes Lingettes OxiGenesis from ENVIROX NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.
WEEE	Please enquire of your local Pressalit subsidiary or distributor (in countries where there is no subsidiary) that will arrange for recycling of electronic waste in accordance with the WEEE directive.

Product	SCT 2000 shower change table, coated mesh cover, electrically height adjustable with wall-mounted safety stop and backup battery
Item number	R8581218000D

Installation in different wall types

	**Concrete >B25** V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
	**Solid Brick >= Mz12** V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
	**Solid Sand Lime Brick >= Hlz12** V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
	**Aerated Concrete P4** V8658 - Mounting kit, 6 coach screws Ø10 x 70 - plugs GB14. To be ordered separately.	
	**Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood** V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.	

Product	SCT 2000 shower change table, coated mesh cover, electrically height adjustable with wall-mounted safety stop and backup battery
Item number	R8581218000D
	**Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood** Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar. 
	**Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)** Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar. 
	**Drywall (2 x 12,5 mm) water-resistant** Mounting in this wall type is not recommended - risk of fatal injury to persons and walls. 

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com