

# PRESSALIT.

## Pressalit Objecta / Projecta / Projecta Plus without cover 53 Standard toilet seat with antibacterial effect, without cover, incl. hinge in stainless steel

Item number Colour Description	<ul> <li>53011-BA1999</li> <li>EAN:5708590321516</li> <li>Pressalit Objecta/Projecta/Projecta Plus - without cover. Project seats are universal seats and contains an antibacterial effect, which prevents the growth of bacteria 24/7. Particularly suited to building projects.</li> <li>White</li> <li>PRESSALIT toilet seat without cover, model "Objecta", art.no. 53 made of colour ingrained duroplast, incl. BA1 fixed hinge in stainless steel.</li> <li>centre distance: 155 mm</li> <li>load - ring seat 240 kg</li> <li>10 year guarantee</li> </ul>	
	415 / 442 370 *55 mm	A4003 A4001 A7222 A7222 A7220
Designer	Pressalit	
Design year	1982	



hinge in stainless stee	51	
Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% ur formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants a moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.	
	POLYGIENE (only relevant for toilet seats with polygiene): Polygiene consists of biocide silver chloride, which has an anti-bacterial effect. Th why the bacteria growth is hampered 24 hours a day.	
	BUFFERS: EVA (copolymer made of ethylene and vinyl acetate).	
	DAMPER KIT (only relevant for toilet seats with soft close): Hydraulic damper with stainless steel damper casing and thermoplastic parts.	
	MOUNT/HINGES: Stainless steel model W. no. 1.4301/M and thermoplastic.	
Product capacity	Load - ring seat 240 kg	
Weight	1,169 kg	
Carton size	457x389x68 mm	
Gross weight	1,569 kg	
Crate size	469x401x348 mm	
Weight per crate	7,845 kg	
Qty per crate	5	
Crates per pallet	18	
Qty per pallet	90	
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, m sure that the seat and cover are kept in an upright position until all cleaning agent ha	



#### Pressalit Objecta / Projecta / Projecta Plus without cover 53 Standard toilet seat with antibacterial effect, without cover, incl. hinge in stainless steel

#### Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

### pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

