

PRESSALIT.

Product Item number	Child changing table, 31.5" x 35.4", electrically height adjustable R8961000		
	EAN: 5708590367224		
Color	White 46.00		
Product description	Pressalit offers a wide variety of changing tables designed for use in daycare facilities. The tables are available in several sizes and models, either free standin wall-hung. The fold away feature in wall-hung tables is useful where space is limit The wall-hang tables with low start are essential for daycare or preschool facilities Even toddlers can climb onto the table themselves, without the staff lifting them. Changing table, wall-mounted, low start, 31.5" x 35.4". With motor and transformer, height adjustable from 11.8" - 39.4", with hand control and safety stop function. Molded worktop, incl. 2 wire baskets. Materials: ABS plastics, synthetic acrylic and powder-lacquered steel. Excl. fixing kit.		
Adjustability	Height adjustable		
Adjustment height	27,58 inch		
Product capacity	Max load: 165 lbs.		
Speed up	Speed up: 1,5 inch/s Speed down: 1,5 inch/s		
Noise level	48 dB		
Materials	Lifting unit and baskets: Powder-laquered steel. Countertop: ABS with acrylic.		
Ergonomy	The smooth height adjustment ensures that it is always possible to set the table at an ergonomically correct height. The table descends to a very low position, which offers the advantage that toddlers can easily climb up and down themselves. Thereby unnecessary lifting is avoided.		



PRESSALIT.®

Product	Child changing table, 31.5" x 35.4", electrically height adjustable	
tem number	R8961000	
Features	Easy-to-clean surfaces ensure optimum hygiene. Integrated safety system prevents entrapment.	
Mains connection (V)	120	
Actuator (motor)	LA31 Deskline (Linak), 2500N, IPX1	
Control box	CBD6 (Linak), IP20	
Wired remote control	HB30 (Linak), IPX4	
Power consumption (maximum load)	Power consumption by maximum load: 96 W Power consumption by standby: 0,1 W	
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.	
Cleaning	This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200	



PRESSALIT®

Product
Item number

Child changing table, 31.5" x 35.4", electrically height adjustable

R8961000

Mounting in different wall types

Mounting in different wall types			
	Concrete >B25 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.		
	Solid Brick >= Mz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.		
	Solid Sand Lime Brick >= HIz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.		
	Aerated Concrete P4 V8658 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs GB14. To be ordered separately.		
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.		



PRESSALIT®

Drywall (2 x 12,5 mm) water-resistant, re-enforced with	
22 mm plywood Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
Drywall (2 x 12,5 mm) water-resistant Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	\wedge
	drywall it is possible to use e.g. SnapTight or WingIt anchors or similar. Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar. Drywall (2 x 12,5 mm) water-resistant Mounting in this wall type is not recommended - risk of

pressalit.com