






**Pressalit Magnum 104**  
**Standard toilet seat incl. fixed hinge in stainless steel**

<p><b>Item number</b></p> <p><b>Colour</b></p> <p><b>Description</b></p>	<p>104030-B33999M          EAN:5708590056678</p> <p>Pressalit Magnum is developed especially for Villeroy &amp; Boch's sanitary programme of the same name.</p> <p>Edelweiss</p> <p>PRESSALIT toilet seat with cover, model "Magnum", art. no. 104 made of colour ingrained duroplast with B33 fixed hinge of stainless steel.</p> <ul style="list-style-type: none"> <li>- centre distance: 155 mm</li> <li>- load - ring seat 240 kg</li> <li>- 10 year guarantee</li> </ul> <div style="display: flex; justify-content: space-around; align-items: flex-start;">    </div>
<p><b>Design type</b></p> <p><b>Designer</b></p> <p><b>Design year</b></p>	<p>Wrap-over</p> <p>Frog Design</p> <p>1987</p>
<p><b>Materials</b></p> <p><b>Product capacity</b></p>	<p><b>TOILET SEAT:</b>          The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing (&lt; 0.01 mg/m³) to emit significantly below the permitted EU limit of 0.08 mg/m³.</p> <p><b>BUFFERS:</b>          EVA (copolymer made of ethylene and vinyl acetate).</p> <p><b>MOUNT/HINGES:</b>          Stainless steel and thermoplastic.</p> <p>Load - ring seat 240 kg</p>
<p><b>Weight</b></p>	<p>3,149 kg</p>



---

**Pressalit Magnum 104**  
**Standard toilet seat incl. fixed hinge in stainless steel**

---

<b>Carton size</b>	490x389x84 mm
<b>Gross weight</b>	3,622 kg
<b>Crate size</b>	500x400x368 mm
<b>Weight per crate</b>	18,11 kg
<b>Qty per crate</b>	5
<b>Crates per pallet</b>	12
<b>Qty per pallet</b>	60
<b>Cleaning</b>	<p>Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.</p>
<b>Warranty</b>	<p>Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.</p> <p>Subject to changes in the product range, technical changes and printing errors.</p>