


PRESSALIT®

Pressalit Magnum 104 Standard toilet seat incl. fixed hinge in stainless steel

Item number	104000-B33999 EAN:5708590024080
	Pressalit Magnum is developed especially for Villeroy & Boch's sanitary programme of the same name.
Colour	White
Description	PRESSALIT toilet seat with cover, model "Magnum",

PRESSALIT toilet seat with cover, model "Magnum", art. no. 104 made of colour ingrained duroplast with B33 fixed hinge of stainless steel.

- centre distance: 155 mm
- load ring seat 240 kg
- 10 year guarantee





MOUNT/HINGES:

Load - ring seat 240 kg

Product capacity

Stainless steel and thermoplastic.





	←──354──→ *35 mm
Design type	Wrap-over
Designer	Frog Design
Design year	1987
Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing (< 0.01 mg/m³) to emit significantly below the permitted EU limit of 0.08 mg/m³. BUFFERS: EVA (copolymer made of ethylene and vinyl acetate). DAMPER KIT (only relevant for toilet seats with soft close): Hydraulic damper with stainless steel damper casing and thermoplastic parts.
	Hydraulic damper with stainless steel damper casing and thermoplastic parts.



PRESSALIT.

Pressalit Magnum 104 Standard toilet seat incl. fixed hinge in stainless steel

Weight 3,149 kg

Carton size 490x389x84 mm

Gross weight 3,622 kg

Crate size 500x400x368 mm

Weight per crate 18,11 kg

Qty per crate 5

Crates per pallet 12

Qty per pallet 60

Cleaning Use a mild soap solution to clean the seat. Please take care that the seat and hinges are

not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has

been flushed away.

Warranty Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of

receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is

not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com