

# PRESSALIT.®

Product	PLUS fold down grab bar with integrated counter-balance, 27.6"		
Item number	R360070000		
	VVS:615871100		
	NRF:6191066		
	RSK:8487436		
	EAN:5708590367859		
	HMI: 123556		
	DB: 2509941		
	FDA: ILS/D135866		
Color	White		
Product description	All PLUS fold down grab bars come with an integrated counter-balance, which ensures a controlled movement between horizontal and vertical positions.  All PLUS fold down grab bars come with an integrated counter-balance, which ensures a controlled movement between horizontal and vertical positions.  Suitable for use with toilet pans projecting 21.3/21.7".  Replaces discontinued models R3060, RF060, R3070 and RF070.  PLUS fold down grab bar, counter-balanced. Projection 27.6", ergonomically shaped to provide a clear sense of where the fold down grab bar ends. For fixed mounting. Foldable.  Materials: The arms are construced of 10-micrometer anodized aluminium, with a non-slip gripping surface made of soft SEBS incorporating a glass-reinforced nylon core Excl. mounting kit.		
Adjustability	Fixed mounting		
Product capacity	Maximum load: 330 lbs. When the fold down grab bar is loaded with 330 lbs, each wall fastener is loaded with 355 lbs.		
	PLUS fold down grab bars have been tested statically with 1540 lbs (close to the wall), 935 lbs (in the middle) and 495 lbs (the outermost point).		



## PRESSALIT.

Product Item number	PLUS fold down grab bar with integrated counter-balance, 27.6" R360070000	
Materials	The grab bars are primarily constructed from 3/8" anodized aluminium, with a non-slight gripping surface at the end made of soft SEBS and incorporating a glass-reinforced nylon core.  The hinge arm is also made of soft SEBS. Internal components and fasteners are primarily made of stainless steel. The hinge barrel is capped with ABS polymer.	
Ergonomy	The oval shape gives an easy and comfortable surface to lean and push against.  The end of the support arm is enlarged so that it is easier to pull forward from a sitting position and also provides a clear sense of where the support arm ends.  Soft and slip-resistant material that has a warm feel.	
Features	Folds against the wall.  The underside is shaped for the mounting of various accessories.	
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.	



## PRESSALIT.

Product	PLUS fold down grab bar with integrated counter-balance, 27.6"		
Item number	R360070000		
Cleaning	This product should be cleaned with hot water or a mild cleaning solution.  Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.		
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.		
	DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% Oxyplus-acid 2% (Diversey) WipeClean UniversalCleaning Chrolorine Disinfection Wipes		
	NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro		
	The product must be wiped down with a soft rag wrung out in clear water immediate after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.		
	DECALCIFICATION OF ALUMINUM PARTS:		

Pressalit recommends that water deposits (Calcium, lime etc.) be removed from wall tracks and other aluminum parts using a solution of three parts of 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts should be wiped over with a damp cloth wrung out in plain water.



# PRESSALIT.®

Product Item number	PLUS fold down grab bar with integrated counter-balance, 27.6" R360070000
	Intended use The fold down grab bar is used as a support for sitting down or getting up from a toilet, or for sideways transfer from a wheelchair.  Operating environment For indoor use in a wet environment, such as a bathroom or a washroom, in private homes, nursing homes and hospitals.  For institutional use, the expected life time is 10 years.  Life cycle test performed according to ISO 17966:2016.
	For maintenance, please refer to operation and maintenance manual, which is enclosed with the product, and which can also be found on the website under "Downloads".  Intended use The fold down grab bar is used as a support for sitting down or getting up from a toilet, or for sideways transfer from a wheelchair.  Operating environment For indoor use in a wet environment, such as a bathroom or a washroom, in private homes, nursing homes and hospitals.  For institutional use, the expected life time is 10 years.
	Life cycle test performed according to ISO 17966:2016.  For maintenance, please refer to operation and maintenance manual, which is enclosed with the product, and which can also be found on the website under

"Downloads".



### PRESSALIT.

<b>Product</b>
----------------

Item number

PLUS fold down grab bar with integrated counter-balance, 27.6"

R360070000

### Mounting in different wall types


In. V ((	
.C	
D . 7 a	
0.0.0.0	
Δ. D. G	

#### Concrete >B25

V8604 - Mounting kit, 4 countersunk bolts  $\emptyset$ 8 x 70, plugs SX10.

To be ordered separately.






#### Solid Brick >= Mz12

V8604 - Mounting kit, 4 countersunk bolts  $\emptyset$ 8 x 70, plugs SX10.

To be ordered separately.





#### **Solid Sand Lime Brick >= HIz12**

V8604 - Mounting kit, 4 countersunk bolts  $\emptyset$ 8 x 70, plugs SX10.

To be ordered separately.







#### **Aerated Concrete P4**

V8654 - Mounting kit, 4 countersunk bolts M8 x 35, plugs FTP M 8.

To be ordered separately.






### Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8604 - Mounting kit, 4 countersunk bolts Ø8 x 70, plugs SX10. NB! Plugs are not needed.

To be ordered separately.





## PRESSALIT®

Product Item number	PLUS fold down grab bar with integrated counter-bal R360070000	ance, 27.6"
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood  Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch)  Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant  Mounting in this wall type is not recommended - risk of	<b>A</b>
	fatal injury to persons and walls.	<u>!</u>

pressalit.com