
PRESSALIT®

Product	SELECT TL1 toilet lifter, for floor outlet
Item number	R8232112
	EAN:5708590339641 FDA: IKX/D319729
Color	Anthracite gray
Product description	The aim is to make it as easy as possible for users to get on and off the toilet during daily use. The aim is also to make the carer's work easier, and make the process comfortable and dignified for the user. **Please contact Pressalit for more information about compatible toilet bowls for Pressalit SELECT toilet lifters** SELECT TL1 toilet lifter, 15.8" electrically height adjustable with wired hand control. Incl. cistern with dual flushing system preset at 3/6 liters. Toilet pan and toilet seat to be ordered separately. For floor-outlet. Materials: Anodised aluminium and polystyrene (PS). Excl. mounting kit.
Adjustability	Height adjustable
Adjustment height	15,76 inch
Product capacity	Maximum user weight: 440 lbs. Maximum load: 518 lbs. (user weight + accessories). When the toilet lifter is loaded with 518 lbs, each wall fastener is loaded with 143 lbs. *The toilet lifter has been tested statically with 1320 lbs, which is a requirement according to the applied assistive products standards. Please note that most toilets compatible with this lifter have been tested up to 880 lbs.*
Speed up	Speed up: 0,47 inch/s Speed down: 0,47 inch/s
Noise level	48 dB




Product	SELECT TL1 toilet lifter, for floor outlet
Item number	R8232112
Materials	Anodized aluminium. The front plates are made of polystyrene (PS). Top plate in compact laminate. *Flammability-tested (ISO 8191-1 and ISO 8191-2). Test report available.*
Ergonomy	Toilet lifters are available in three different colors to match many bathroom decors. Also helping to create a soothing color palette in the room. A minimum of grooves, slots and holes makes cleaning fast and effective, and also results in an attractive and exclusive design.
Features	The toilet lifter is available with a wired hand control which makes it easy for the user or caregiver to adjust the height. Seat height can be adjusted a full 15.8" from 16.7" to 32.5" – even while the user is sitting on the toilet.
Mains connection (V)	120
Actuator (motor)	LA31 Careline, (Linak), 4000N, IPX6
Control box	CB9 Careline, (Linak), IPX6
Wired remote control	HB7, (Linak) IP66
Power consumption (maximum load)	Power consumption by maximum load: 70 W Power consumption by standby: 2 W
Warranty	A 5-year warranty is provided for your product from the date of purchase. The warranty covers material or manufacturing defects. The warranty does not cover defects or damage resulting from normal wear and tear, improper operation, misuse, inadequate maintenance, use of unsuitable cleaning agents, incorrect installation, or disassembly. In the event of a claim, you must always contact the dealer or store where you purchased the product. The warranty is conditional upon proof of purchase of the product. Pressalit will supply a spare part or replace the product with the same or a similar model. The warranty period is neither extended nor renewed when replacement products or spare parts are supplied. If replacement is not possible, Pressalit is entitled instead to refund the purchase price. These warranty terms apply in addition to the consumer's statutory rights and do not limit or exclude them.

Product	SELECT TL1 toilet lifter, for floor outlet
Item number	R8232112
Cleaning	This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate. DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that water deposits (Calcium, lime etc.) be removed from wall tracks and other aluminum parts using a solution of three parts of 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts should be wiped over with a damp cloth wrung out in plain water.
WEEE	Please enquire of your local Pressalit subsidiary or distributor (in countries where there is no subsidiary) that will arrange for recycling of electronic waste in accordance with the WEEE directive.

PRESSALIT®


Product	SELECT TL1 toilet lifter, for floor outlet
Item number	R8232112


Mounting in different wall types



Concrete >B25


V8605 - Mounting kit, 4 lag bolts Ø10 x 70, plugs SX12, with grey covers.
To be ordered separately.






Solid Brick >= Mz12


V8605 - Mounting kit, 4 lag bolts Ø10 x 70, plugs SX12, with grey covers.
To be ordered separately.






Solid Sand Lime Brick >= Hlz12


V8605 - Mounting kit, 4 lag bolts Ø10 x 70, plugs SX12, with grey covers.
To be ordered separately.






Aerated Concrete P4


V8655 - Mounting kit, 4 lag bolts Ø10 x 70, plugs GB14, with grey covers.
To be ordered separately.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8605 - Mounting kit, 4 lag bolts Ø10 x 70, plugs SX12, with white covers. NB! Plugs are not needed.
To be ordered separately.





Product	SELECT TL1 toilet lifter, for floor outlet
Item number	R8232112



Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood


Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch)

Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.





Drywall (2 x 12,5 mm) water-resistant

Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.



It is the responsibility of the installer to ensure that suitable wall fasteners are used.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com