



<b>Product</b>	PLUS wash basin bracket with wired hand control, electrically height adjustable and manually sideways adjustable
<b>Item number</b>	R4781
	VVS:654003220 NRF:6132538 RSK:7972596 EAN:5708590309347 HMI: 71755 NBS:N13:30,335 FDA:ILW/D142473
<b>Product description</b>	<p>PLUS wash basin brackets are available in electrically, pneumatically and manually height adjustable versions.</p> <p>They are suitable for wall-mounting or for fitting to Pressalit PLUS wall tracks.</p> <p>PLUS wash basin bracket, powered with wired remote control, electrically height adjustable by 300 mm and sideways adjustable. Recommendation: Flexible feed and waste system R2064/R2065/R2067. (UK markets R2074/R2075/R2077). Materials: Aluminium and ABS polymer. Incl. fixing bolts for wash basin. For fitting to horizontal PLUS wall track (not included).</p>
<b>Adjustability</b>	Height and sideways adjustable
<b>Adjustment height</b>	300 mm
<b>Product capacity</b>	<p>Maximum load: 100 kg. Suitable for wash basins weighing no more than 22 kg. When the wash basin is loaded with 100 kg, each wall fastener will be carrying 22 kg. <i>Wash basin brackets need to be able to carry the weight of the wash basin, as well as support the weight of the person who is leaning against the wash basin or who is using the wash basin to rise from seated position.</i></p> <p><b><i>Neither wash basin nor wash basin bracket are intended to carry the full body weight of a person, and the test methods applicable to wash basin brackets reflect this: ISO 17966 prescribes a static test on the front edge of the wash basin at 75% of maximum user weight, i.e. when the maximum load on a wash basin bracket is given as 100 kg and the wash basin weighs 22 kg, it is – according to ISO 17966 – the equivalent of a user weighing 104 kg leaning on the front edge of the wash basin.</i></b></p>



<b>Product</b>	PLUS wash basin bracket with wired hand control, electrically height adjustable and manually sideways adjustable
<b>Item number</b>	R4781
<b>Speed upwards</b>	Speed up mm: 20 mm/s Speed down mm: 23 mm/s
<b>Noise level</b>	45 dB
<b>Materials</b>	The wash basin bracket is primarily made of 10-micrometre anodized aluminium. The ends of the bracket cover are capped with ABS polymer. The brackets are available with a wired hand control encased in polypropylene.
<b>Ergonomics</b>	The height of the wash basin is easily adjusted by means of the wired hand control. The wash basin bracket suits all types of bolt-mounted wash basin. Its rounded, sleek design greatly facilitates cleaning.
<b>Features</b>	An independent user will be able to make the necessary adjustments to an electrically operated wash basin bracket themselves without any problems.
<b>Mains connection (V)</b>	230
<b>Actuator (motor)</b>	LA40 (Linak) 4000N, IPX6
<b>Control box</b>	SMPS14002
<b>Wired remote control</b>	HB3 (Linak) IPX6
<b>Power consumption (maximum load)</b>	Power consumption by maximum load, watt: 75 W Power consumption by standby: 1,5 W
<b>Warranty</b>	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.



<b>Product</b>	PLUS wash basin bracket with wired hand control, electrically height adjustable and manually sideways adjustable
<b>Item number</b>	R4781
<b>Cleaning</b>	<p>PLUS &amp; SELECT wash basin brackets</p> <p>The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.</p> <p>The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.</p> <p><b>DISINFECTANTS:</b> Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättssprit 70%</p> <p><b>NON-DISINFECTANTS:</b> Suma Star free D1 Taski 100 Taski 200 Milizid Citro</p> <p>The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.</p> <p><b>DECALCIFICATION OF ALUMINUM PARTS:</b> Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts must be wiped over with a damp cloth wrung out in clear water.</p>
<b>WEEE</b>	Please enquire of your local Pressalit subsidiary or distributor (in countries where there is no subsidiary) that will arrange for recycling of electronic waste in accordance with the WEEE directive.



# PRESSALIT®

---

<b>Product</b>	PLUS wash basin bracket with wired hand control, electrically height adjustable and manually sideways adjustable
<b>Item number</b>	R4781

---

---

[pressalit.com](http://pressalit.com)

---

Pressalit A/S  
Pressalitvej 1  
DK-8680 Ry  
Tel.: +45 8788 8788  
Fax: +45 8788 8789  
E-mail: [pressalit@pressalit.com](mailto:pressalit@pressalit.com)

# PRESSALIT®