

PRESSALIT.

Product	MATRIX manual basin unit, right-facing, height adjustable		
Item number	R4840000		
	VVS:654021300		
	EAN:5708590340890		
	HMI: 137779		
	FDA: ILW/D142473		
Colour	White max 710 min 510		
Product description	MATRIX brackets are tailor made for MATRIX wash basins. They are available in electrically and manually height adjustable and sideways adjustable versions, as well as fixed versions, all of them with a hygienic cover to conceal the plumbing installations.		
	MATRIX wash basin bracket, right-facing, wall-mounted, with white installation cover and incl. concealed flexible feed/waste system. br Incl. fixing bolts for wash basin (Can only be used with MATRIX ANGLE DEEP wash basins, R2140/R2141). Materials: Powder-coated stainless steel and PMMA. Excl. mounting kit.		
Adjustability	Height adjustable		
Adjustment height	200 mm		
Product capacity	Maximum user weight (MUM): 160 kg. Maximum load (SWL): 150 kg. Suitable for wash basins that weigh 30 kg. When the wash basin is loaded with 150 kg, each wall fastener will be carrying 60 kg. Wash basin brackets need to be able to carry the weight of the wash basin, as well as support the weight of the person who is leaning against the wash basin or who is using the wash basin to rise from seated position. Neither wash basin nor wash basin brackets are intended to carry a person, and the test methods applicable to wash basin brackets reflect this: ISO 17966 prescribes a static test on the front edge of the wash basin at 75% of maximum user weight, i.e. when the maximum load on a wash basin bracket is given as 150 kg and the wash basin weighs 30 kg, it is – according to ISO 17966 – the equivalent of a user weighing 160 kg leaning on the front edge of the wash basin.		
Materials	Powder-coated stainless steel and PMMA.		



PRESSALIT.®

Product	MATRIX manual basin unit, right-facing, height adjustable		
Item number	R4840000		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.		
Cleaning	VALUE & MATRIX wash basin brackets The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use corrosive or abrasive cleaners as it may result in the surface being damaged. For surface disinfection, chlorine-based disinfectants may be used according to the product specification and safety precautions for these products. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Millizid Citro The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the		
Declaration of	surface coating may deteriorate. CE MDR-MASK This product is in compliance with all relevant requirements of:		
conformity	- Regulation (EU) 2017/745 on medical devices - Council Directive 2006/42/EC on machinery		



PRESSALIT®

Product		
Item number		

MATRIX manual basin unit, right-facing, height adjustable

R4840000

Installation in different wall types

Concrete >B25 V8605 - Mounting kit, 4 coach screws Ø10 x 70, plugs SX12, with grey screw covers. To be ordered separately.	
Solid Brick >= Mz12 V8605 - Mounting kit, 4 coach screws Ø10 x 70, plugs SX12, with grey screw covers. To be ordered separately.	
Solid Sand Lime Brick >= HIz12 V8605 - Mounting kit, 4 coach screws Ø10 x 70, plugs SX12, with grey screw covers. To be ordered separately.	
Aerated Concrete P4 V8655 - Mounting kit, 4 coach screws Ø10 x 70, plugs GB14, with grey screw covers. To be ordered separately.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8605 - Mounting kit, 4 coach screws Ø10 x 70, plugs SX12, with white screw covers. NB! Plugs are not needed. To be ordered separately.	



PRESSALIT®

Product Item number	MATRIX manual basin unit, right-facing, height adjustable R4840000
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.
基础数据	Drywall (2 x 12,5 mm) water-resistant Wall fasteners (4 pcs) must be bought separately, for
	drywall it is possible to use e.g. fischer KD8 toggles or similar.

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com