

# PRESSALIT.

Product Item number	Changing table, 31.5" x 55.1", electrically height adjustable, foldable R8972000	
Color	EAN: 5708590367262  White	
Product description	Pressalit offers a wide variety of changing tables designed for use in daycare facilities. The tables are available in several sizes and models, either free standing or wall-hung. The fold away feature in wall-hung tables is useful where space is limited. The wall-hang tables with low start are essential for daycare or preschool facilities. Even toddlers can climb onto the table themselves, without the staff lifting them.  Changing table, wall-mounted, low start, foldable, 31.5" x 55.1".  With motor and transformer, height adjustable from 11.8" - 39.4", with hand control. Materials: Molded worktop in ABS plastics, synthetic acrylic and powder-lacquered steel.  Excl. fixing kit.	
Adjustability	Height adjustable	
Adjustment height	27,58 inch	
Product capacity	Max load: 165 lbs.	
Speed up	Speed up: 1,5 inch/s Speed down: 1,5 inch/s	
Noise level	48 dB	
Materials	Lifting unit: Powder-coated steel. Countertop: ABS with acrylic.	
Ergonomy	The smooth height adjustment ensures that it is always possible to set the table at an ergonomically correct height.  The table descends to a very low position, which offers the advantage that toddlers can easily climb up and down themselves. Thereby unnecessary lifting is avoided.	



# PRESSALIT.

Product Item number	Changing table, 31.5" x 55.1", electrically height adjustable, foldable R8972000
Features	Easy-to-clean surfaces ensure optimum hygiene.  The integrated pneumatic cylinder enables the table to be folded easely against the wall when not in use to maximize floor space.  Integrated safety system prevents entrapment.
Mains connection (V)	120
Actuator (motor)	LA31 Deskline (Linak), 2500N, IPX1
Control box	CBD6 (Linak), IP20
Wired remote control	HB30 (Linak), IPX4
Power consumption (maximum load)	Power consumption by maximum load: 96 W Power consumption by standby: 0,1 W
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.
•	



## PRESSALIT®

Product	Changing table, 31.5" x 55.1", electrically height adjustable, foldable		
ltem number	R8972000		
Cleaning			
	This product should be cleaned with hot water or a mild cleaning solution.  Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.		
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.		
	DISINFECTANTS:		
	Clinimax Difficil-S		
	Erisan OXY+ Sprit (husholdningssprit)		
	Suma Bac D10		
	Virkon		
	Rodalon Desinfektionsspray		
	Lysoformin Spezial		
	CaviCide		
	Sufanios Premium Tvättsprit 70%		
	NON-DISINFECTANTS:		
	Suma Star free D1		
	Taski 100		
	Taski 200		
	Milizid Citro		
	The product must be wiped down with a soft rag wrung out in clear water immedia		
	after also with a second restantial mean after with a discolored and state and and a		

surface coating may deteriorate.

after cleaning, as some materials may otherwise be discolored and stained, and the



#### PRESSALIT®

Product					
Item	numbe				

Changing table, 31.5" x 55.1", electrically height adjustable, foldable R8972000

#### Mounting in different wall types

wounting in different wall types				
	Concrete >B25 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.			
	Solid Brick >= Mz12  V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12.  To be ordered separately.			
	Solid Sand Lime Brick >= HIz12  V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12.  To be ordered separately.			
	Aerated Concrete P4  V8658 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs GB14.  To be ordered separately.			
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood  V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12.  NB! Plugs are not needed.  To be ordered separately.			



### PRESSALIT®

Product Item number	Changing table, 31.5" x 55.1", electrically height adju	ustable, foldable
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood  Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch)  Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant  Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	$\wedge$
	fatal injury to persons and walls.	<u>!</u>

pressalit.com