

## PRESSALIT.

I				
Product	Changing table, 800 x 900 mm, electrically height adjustable			
Item number	R8661000			
	VVS:777636010			
	NRF:7501974			
	EAN:5708590338354			
	HMI: 100176			
Colour	White 1169 900			
Product description	essalit offers a wide range of daycare changing tables, both free-standing and walling, in several sizes and models. The wall-hung tables are also available in versions here the worktop folds away, which are suitable for rooms with limited space. If particular use to daycare facilities and kindergartens are the low start wall-hung anging tables, which can be lowered to a height that allows children to climb onto be worktop themselves. If types of daycare changing tables are available in versions with sanitary appliances and a choice of taps, with or without pull-out shower heads.			
	Low start, wallhung changing table, 800 x 900 mm. With electric motor and transformer, height adjustable from 300 mm - 1000 mm, wi wired hand control and safety stop function. Molded worktop, incl. 2 wire baskets. Materials: ABS plastics, synthetic acrylic and powder-lacquered steel. Excl. mounting kit.			
Adjustability	Height adjustable			
Adjustment height	700 mm			
Product capacity	Max load: 75 kg.			
Speed upwards	Speed up mm: 38 mm/s Speed down mm: 38 mm/s			
Noise level	48 dB			
Materials	Lifting unit and baskets: Powder-laquered steel. Worktop: ABS with acrylic.			



### PRESSALIT.

Product	Changing table, 800 x 900 mm, electrically height adjustable		
Item number	R8661000		
Ergonomy	The smooth height adjustment ensures that it is always possible to set the table at an ergonomically correct height.  The table descends to a very low position, which offers the advantage that toddlers can easily climb up and down themselves.  Thereby unnecessary lifting is avoided.		
Features	Easy-to-clean surfaces ensure optimum hygiene. Integrated safety system prevents entrapment.		
Mains connection (V)	230		
Actuator (motor)	LA31 Deskline (Linak), 2500N, IPX1		
Control box	CBD6 (Linak), IP20		
Wired remote control	HB30 (Linak), IPX4		
Power consumption (maximum load)	Power consumption by maximum load, watt: 96 W Power consumption by standby: 0,1 W		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.		



# PRESSALIT.

Product	Changing table, 800 x 900 mm, electrically height adjustable
Item number	R8661000
Cleaning	Daycare changing tables The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.  The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.  DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70%  NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro
Declaration of conformity	The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.  CE UK MASK-ROHS This product complies with the relevant requirements of:  - Council Directive 2006/42/EC on machinery  - Council Directive 2011/65/EC on RoHS.  For the UK: - The Supply of Machinery (Safety) Regulations 2008  - Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012



#### PRESSALIT®

Product		
Item number		

Changing table,  $800 \times 900 \text{ mm}$ , electrically height adjustable

R8661000

#### Installation in different wall types

 <b>. . . . . . . . . .</b>	
Concrete >B25  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Solid Brick >= Mz12  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Solid Sand Lime Brick >= Hlz12  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Aerated Concrete P4  V8658 - Mounting kit, 6 coach screws Ø10 x 70 - plugs GB14.  To be ordered separately.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs  SX12. NB! Plugs are not needed.  To be ordered separately.	



### PRESSALIT®

Product Item number	Changing table, 800 x 900 mm, electrically height ad R8661000	justable
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood  Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)  Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant  Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	<u>^</u>

pressalit.com