PRESSALIT®

Product	MATRIX CURVE II ergonomic sink with tap hole, without overflow
Item number	R2053000
	VVS:636862200 NRF:6132514 RSK:7503002 EAN:5708590333878 HMI: 101016
Color	White
Product description	MATRIX is a series of sinks, most of them are designed by Pressalit. MATRIX SMALL and CURVE sinks fit onto PLUS, SELECT and VALUE sink brackets, whereas MATRIX MEDIUM and ANGLE are tailor made to fit specific brackets. MATRIX CURVE II ergonomic sink, 23.6" x 19.2" x 5.9", with tap hole diameter 1.4", without overflow. Supplied with drain fitting. The concave front edge stabilises standing as well as seated users. The rounded edges are also comfortable to hold and rest against. The flat bottom leaves room for the legs underneath. Material: Ceramic. Suitable for sink brackets from the Pressalit PLUS, SELECT and VALUE ranges.
Product capacity	330 lbs.
Materials	Ceramic
Ergonomy	The concaved front edge stabilizes a standing as well as a seated user. The rounded shapes are nice to grip and lean against. The design of the corners leaves space and supports the elbows in the sink and the flat bottom leaves space for the legs of a seated user.
Warranty	A 5-year warranty is provided for your product from the date of purchase. The warranty covers material or manufacturing defects. The warranty does not cover defects or damage resulting from normal wear and tear, improper operation, misuse, inadequate maintenance, use of unsuitable cleaning agents, incorrect installation, or disassembly. In the event of a claim, you must always contact the dealer or store where you purchased the product. The warranty is conditional upon proof of purchase of the product. Pressalit will supply a spare part or replace the product with the same or a similar model. The warranty period is neither extended nor renewed when replacement products or spare parts are supplied. If replacement is not possible, Pressalit is entitled instead to refund the purchase price. These warranty terms apply in addition to the consumer's statutory rights and do not limit or exclude them.

Product	MATRIX CURVE II ergonomic sink with tap hole, without overflow
Item number	R2053000
Cleaning	For cleaning the wash basin, use hot water and a mild soapy cleaning agent. Make sure that the product is wiped down with a soft rag wrung out in clear water immediately after cleaning. For disinfecting the wash basin, the following agents can be used: Sodium hydroxide 5% Acetic acid solution 10% Ethanol solution 70% Sodium hypochlorite 5%, active chlorine Sodium chloride 170g/l, diluted to 50%. Make sure that the product is wiped down with a soft rag wrung out in clear water immediately after disinfection. **NB! Do not use abrasive cleaning agents, as this will cause damage to the surface of the wash basin.**

PRESSALIT®

Product	MATRIX CURVE II ergonomic sink with tap hole, without overflow
Item number	R2053000

Mounting in different wall types



Concrete >B25

V8602 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs SX12.
To be ordered separately





Solid Brick >= Mz12

V8602 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs SX12.
To be ordered separately





Solid Sand Lime Brick >= Hlz12

V8602 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs SX12.
To be ordered separately





Aerated Concrete P4

V8652 - Mounting kit, 2 lag bolts Ø10 x 100 - plugs GB14.
To be ordered separately.





Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8602 - Mounting kit, 2 countersunk bolts Ø10 x 80, plugs SX12. NB! Plugs are not needed.
To be ordered separately.



Product	MATRIX CURVE II ergonomic sink with tap hole, without overflow
Item number	R2053000



Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood

Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.



Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch)

Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.



Drywall (2 x 12,5 mm) water-resistant

Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com