
Pressalit Project 300 Pro 1194
Toilet seat with soft close, lift-off and antibacterial effect, incl. hinge in stainless steel


Features	Lift-off, Soft close
Item number	1194111-DH9999 EAN:5708590394480




Pressalit Project 300 Pro – durable design with a modern finish. The Pressalit Project 300 Pro toilet seat with lid is designed for high-traffic environments that demand both durability and aesthetics. The toilet seat combines sleek lines in black or white with our patented SteadyFix® hinges for exceptional stability. Easy to clean and available with lift-off or fixed mounting, it's the ideal solution where both hygiene and visual appeal matter. Available with or without Soft close.

Colour	Black (RAL 9005)
Description	PRESSALIT toilet seat with cover, model "Pressalit Project 300 Pro", art. no. 1194 made of colour ingrained duroplast, with built-in soft close function, incl. DH9 hinge with lift-off in stainless steel. - dismounting of seat/cover makes cleaning easier - centre distance: 155 mm - load - ring seat 240 kg - 10 year guarantee







Design type	Sandwich
Designer	Pressalit
Design year	2024

Pressalit Project 300 Pro 1194
Toilet seat with soft close, lift-off and antibacterial effect, incl. hinge in stainless steel

Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde). UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing (< 0.01 mg/m³) to emit significantly below the permitted EU limit of 0.08 mg/m³. ANTIBACTERIAL: This toilet seat features an antibacterial additive with biocidal silver phosphate glass, which helps prevent bacterial growth. BUFFERS: EVA (copolymer made of ethylene and vinyl acetate). DAMPER KIT: Hydraulic damper with damper housing in stainless steel or thermoplastic, mounted with plastic parts in thermoplastic. MOUNT/HINGES: Stainless steel and thermoplastic.
Product capacity	Load - ring seat 240 kg
Weight	2,74 kg
Carton size	488x388x72 mm
Gross weight	3,164 kg
Crate size	500x400x368 mm
Weight per crate	15,82 kg
Qty per crate	5
Crates per pallet	18
Qty per pallet	90
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.

Pressalit Project 300 Pro 1194
Toilet seat with soft close, lift-off and antibacterial effect, incl. hinge in stainless steel

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com