



PRESSALIT®

Pressalit Code 778
Toilet seat with soft close, incl. hinge in stainless steel

Features

Soft close

Item number

778000-DD7999
 VVS:615057000
 NRF:6190087
 RSK:7904528
 EAN:5708590331331

Pressalit Code means excellent fit and soft contours.
 The toilet seat is especially designed for the D-Code series from Duravit.




Colour

White

Description

PRESSALIT toilet seat with cover, model "Pressalit Code", art. no. 778 made of colour ingrained duroplast with DD7 universal hinge of stainless steel.

- centre distance: 145 - 190 mm
- load - ring seat 180 kg
- suitable for Duravit D-Code
- 10 year guarantee



Design type

Sandwich

Designer

Pressalit

Design year

2012



Pressalit Code 778
Toilet seat with soft close, incl. hinge in stainless steel

Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises approx. 70% urea formaldehyde resin, 30% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. Free formaldehyde is released during the production process. Pressalit toilet seats have been measured after curing (< 0.01 mg/m³) to emit significantly below the permitted EU limit of 0.08 mg/m³. BUFFERS: EVA (copolymer made of ethylene and vinyl acetate). DAMPER KIT: Hydraulic damper with damper housing in stainless steel or thermoplastic, mounted with plastic parts in thermoplastic. MOUNT/HINGES: Stainless steel and thermoplastic.
Product capacity	Load - ring seat 180 kg
Weight	2,53 kg
Carton size	488x388x72 mm
Gross weight	2,955 kg
Crate size	500x400x368 mm
Weight per crate	14,775 kg
Qty per crate	5
Crates per pallet	18
Qty per pallet	90
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



PRESSALIT®

Pressalit Code 778**Toilet seat with soft close, incl. hinge in stainless steel**

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

PRESSALIT®