

PRESSALIT.®

Product	SCT 2000 shower change table, coated mesh cover, fixed height		
Item number	R8425218000		
	VVS:777543020		
	EAN:5708590372167	70.87	
	HMI: 130360		
	FDA: INT/D124320		
Color	White	11.81	
Product description	shower and changing tables of high q platform for showering and changing These tables can be used in schools, are all designed to be durable, comfor The design and flexibility of the tables		
Adjustability	Fixed mounting		
Product capacity	Maximum user weight (MUM): 386 lbs. Maximum load (SWL): 386 lbs. When the table is loaded with 386 lbs, each mounting bolt supports 115 lbs. This product has been tested statically with a load of 579 lbs as the ISO 17966 standard requires testing with a safety factor 1.5.		
Materials	Construction in powder-laquered stainless steel, mesh cover in PVC-coated polyest (for extra durability) and water collection tray in PVC-U.		
Ergonomy	The 2000 series changing table has a low start position to make transfers to the table easier. The washable, perforated mesh cover lets the water pass through to the water collection tray underneath. The flexibility of the changing table provides for optimal working conditions for the carer as well as a high level of comfort and safety for the user.		



PRESSALIT®

Product	SCT 2000 shower change table, coated mesh cover, fixed height
Item number	R8425218000
Features	A water collection tray with integrated water outlet prevents water from splashing on caregiver or the floor. The flexible hose attached to the center mounted outlet of the water collection tray, can be connected to either an outlet in the floor or on the wall. The integrated pneumatic cylinders enable the table to be folded out of the way whe not in use to maximize floor space in front of the unit. The stretcher of the table is very easy to clean, and the stretcher cover can be unzipped for washing or easy replacement.
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. NOTICE If the product is placed in an atmosphere heavy in salt or chloride, the warranty will be reduced from the normal 3 years to 1 year. Salt and chloride have a corrosive effect on the products components and will cause a decrease in the life expectancy of the product.
Cleaning	
	This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.
	DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon
	Rodalon Desinfektionsspray Lysoformin Spezial CaviCide
	Sufanios Premium Tvättsprit 70% Accel PREVention Wipes Lingettes OxiGenesis from ENVIROX
	NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro
	The product must be wiped down with a soft rag wrung out in clear water immediate after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.



PRESSALIT®

Product				
ltem	numbe			

SCT 2000 shower change table, coated mesh cover, fixed height

R8425218000

Mounting in different wall types

Mounting in different wall types				
	Concrete >B25 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.			
	Solid Brick >= Mz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.			
	Solid Sand Lime Brick >= HIz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.			
	Aerated Concrete P4 V8658 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs GB14. To be ordered separately.			
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.			



PRESSALIT®

Product Item number	SCT 2000 shower change table, coated mesh cover, R8425218000	, fixed height
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant	
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	!

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789

PRESSALIT.