



**Pressalit Projecta Solid Pro without cover 1003**  
**Toilet seat with soft close and Polygiene®, without cover, incl.**  
**Solid Pro hinge**

**Features**

Soft close

**Item number**

1003111-DG4925  
 EAN:5708590344683

Pressalit Projecta Solid Pro - without cover. A design-conscious choice for the project market. With an antibacterial Polygiene effect and strong fittings that ensure optimum stability - even during sideways transfer. The market's first institution seat with integrated soft closing function.






**Colour**

Black (RAL 9005)

**Description**

PRESSALIT toilet seat without cover, model "Projecta Solid Pro", art.no. 1003 made of colour ingrained duroplast, incl. DG4 combi hinge, universal.  
 - built-in soft close function  
 - centre distance: 145-210 mm  
 - load - ring seat 240 kg  
 - 10 year guarantee



**Design type**

Sandwich

**Designer**

Pressalit

**Design year**

2016



---

**Pressalit Projecta Solid Pro without cover 1003**  
**Toilet seat with soft close and Polygiene®, without cover, incl.**  
**Solid Pro hinge**

---

**Materials**

**TOILET SEAT:**

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

**POLYGIENE (only relevant for toilet seats with polygiene):**

Polygiene consists of biocide silver chloride, which has an anti-bacterial effect. This is why the bacteria growth is hampered 24 hours a day.

**BUFFERS:**

EVA (copolymer made of ethylene and vinyl acetate).

**DAMPER KIT (only relevant for toilet seats with soft close):**

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

**MOUNT/HINGES:**

Stainless steel model W. no. 1.4301/M, thermoplastic semi-crystalline polyamides with partially aromatic content. Aluminium profile EN AW-6063-TS.

**Product capacity**

Load - ring seat 240 kg

---

**Weight**

1,466 kg

**Carton size**

490x389x84 mm

**Gross weight**

1,806 kg

**Crate size**

517x399x456 mm

**Weight per crate**

9,03 kg

**Qty per crate**

5

**Crates per pallet**

8

**Qty per pallet**

40

**Cleaning**

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



PRESSALIT®

---

**Pressalit Projecta Solid Pro without cover 1003**  
**Toilet seat with soft close and Polygiene®, without cover, incl.**  
**Solid Pro hinge**

---

**Warranty**

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

---

[pressalit.com](http://pressalit.com)

---