Product	Lift for countertop, manually height adjustable
Item number	RK1111
	EAN:5708590292762 HMI: 54800
Product description	Pressalit INDIVO lifting units can be easily integrated into the private home, ensuring that the whole family can enjoy the full potential and use the height adjustable function. The lifting units can also help provide a flexible kitchen solution for e.g. care centers, school kitchens and school science labs, wherever there is a need for frequent height adjustments on kitchen countertops and wall cabinets. Manual lift for countertop Lift for countertop, with a crank handle Including 2 brackets Lengths from 39.4"-55.1". Height adjustable 11.8". Incl. mounting kit for brick wall Please state desired length when ordering
Adjustability	Height adjustable
Product capacity	Maximum load (evenly distributed): 220 lbs including countertop.
Materials	Material: Telescopic leg: Aluminium, ABS plastic Cross braces: Aluminium Brackets: Steel Crank handle: Steel Surface treatment: Brackets: Powder lacquered (grey RAL 9006)
Ergonomy	Kitchen countertops which can be adjusted in height using a crank handle are the budget solution for kitchens catering to both seated and standing users. These are most commonly used in kitchens which do not require frequent, daily adjustment.


PRESSALIT®

Product	Lift for countertop, manually height adjustable
Item number	RK1111
Features	Manual lifts are adjusted in height using a crank handle. They can be used with countertops, with or without an edge. The crank handle socket can be positioned anywhere along the front edge, except under a sink or hob. Lifts can be adapted to most standard kitchen components. Lifts are available for countertops of any length between 23.6" and 118.1". Height adjustable 11.8".
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.
Cleaning	This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate. DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that water deposits (Calcium, lime etc.) be removed from wall tracks and other aluminum parts using a solution of three parts of 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts should be wiped over with a damp cloth wrung out in plain water.

PRESSALIT®


Product	Lift for countertop, manually height adjustable
Item number	RK1111


Mounting in different wall types



Concrete >B25


V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12.
To be ordered separately.






Solid Brick >= Mz12


V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12.
To be ordered separately.






Solid Sand Lime Brick >= Hlz12


V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12.
To be ordered separately.






Aerated Concrete P4


V8658 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs GB14.
To be ordered separately.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12.
NB! Plugs are not needed.
To be ordered separately.





Product	Lift for countertop, manually height adjustable
Item number	RK1111



Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood


Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch)


Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.





Drywall (2 x 12,5 mm) water-resistant

Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.



It is the responsibility of the installer to ensure that suitable wall fasteners are used.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com