





PRESSALIT®

Pressalit Delight 492 Toilet seat with soft close incl. hinge in stainless steel.

Item number	492000-D09999 EAN:5708590282091
Color	White
Description	<p>Discreet. Design. Delicious. The description is that simple. Delight takes the D at face value and fits it to most D-shaped pans. Wrap-over underlines the stringent design, and the soft close function makes it a pleasure to use.</p> <p>PRESSALIT toilet seat with cover, model "Delight", art. no. 492 made of colour ingrained duroplast with D09 universal flex hinge of stainless steel and plastic.</p> <ul style="list-style-type: none"> - centre distance: 135 - 215 mm - load - ring seat 240 kg - suitable for D-shaped toilets - 10 year guarantee
Design type	Wrap-over
Designer	Pressalit
Design year	2007
Materials	<p>TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.</p> <p>BUFFERS: EVA (copolymer made of ethylene and vinyl acetate).</p> <p>DAMPER KIT (only relevant for toilet seats with soft close): Hydraulic damper with stainless steel damper casing and thermoplastic parts.</p> <p>MOUNT/HINGES: Stainless steel model W. no. 1.4301/M and thermoplastic.</p>





PRESSALIT®

Pressalit Delight 492
Toilet seat with soft close incl. hinge in stainless steel.

Product capacity	Load - ring seat 240 kg
Weight	3,345 kg
Carton size	490x389x84 mm
Gross weight	3,553 kg
Crate size	502x401x428 mm
Weight per crate	17,765 kg
Qty per crate	5
Crates per pallet	12
Qty per pallet	60
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.
Warranty	<p>Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.</p> <p>In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.</p> <p>Subject to changes in the product range, technical changes and printing errors.</p>

pressalit.com
