



**Pressalit T Soft 742**  
**Toilet seat with soft close incl. hinge in stainless steel**

**Features**

Soft close

**Item number**

742000-D02999  
 VVS:615001000  
 NRF:6190108  
 EAN:5708590297910

T Soft is a silent and smooth pleasure with built-in soft close to ensure a smooth landing on the toilet. The design is a classic Pressalit design with a perfect finish that makes T Soft cleaning-friendly and an extraordinary experience for the user.






**Colour**

White

**Description**

PRESSALIT toilet seat with cover, model "T Soft", art. no. 742 made of colour ingrained duroplast with D02 universal flex toggle hinge of stainless steel.

- centre distance: 133 - 218 mm
- load - ring seat 240 kg
- suitable for many universal toilets
- 10 year guarantee



**Design type**

Sandwich

**Designer**

Pressalit

**Design year**

2010



---

**Pressalit T Soft 742**  
**Toilet seat with soft close incl. hinge in stainless steel**

---

**Materials**

**TOILET SEAT:**

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

**BUFFERS:**

EVA (copolymer made of ethylene and vinyl acetate).

**DAMPER KIT (only relevant for toilet seats with soft close):**

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

**MOUNT/HINGES:**

Stainless steel model W. no. 1.4301/M and thermoplastic.

**Product capacity**

Load - ring seat 240 kg

---

**Weight**

2,62 kg

**Carton size**

490x389x84 mm

**Gross weight**

3,045 kg

**Crate size**

502x401x428 mm

**Weight per crate**

15,225 kg

**Qty per crate**

5

**Crates per pallet**

12

**Qty per pallet**

60

**Cleaning**

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



PRESSALIT®

---

**Pressalit T Soft 742**  
**Toilet seat with soft close incl. hinge in stainless steel**

---

**Warranty**

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

---

[pressalit.com](http://pressalit.com)

---