

PRESSALIT.

Product	VALUE support arm, fixed height	
Item number	R1100000	
	VVS:615722300	
	NRF:6191642	
	RSK:7972410	
	EAN: 5708590176406	
	HMI: 25411	
	NBS:N13:436	
	DB: 2076622	
	FDA: ILS/D135866	
Colour	White	
Product description	VALUE support arm, fixed, foldable, projection 850 mm. The ergonomic design gives a secure and comfortable grip as well as a good sens of where the support arm ends. Incl. fixing bolts for brick wall. Plugs depend on wall type and must be ordered separately. VALUE support arm, fixed, foldable, projection 850 mm. The ergonomic design gives a secure and comfortable grip as well as a good sens of where the support arm ends. Materials: Rilsan-coated steel, pressure-cast aluminium, plastic. Incl. fixing bolts for brick wall. Plugs depend on wall type and must be ordered separately.	
Adjustability	Fixed mounting	
Product capacity	Maximum load: 120 kg. When the support arm is loaded with 120 kg, each wall fastener is loaded with 242 kg.	
Materials	The support arm is manufactured from steel with a Rilsan coating, which is comfortable to the touch, easy to clean, and protects the metal against corrosion. The end caps are manufactured from nylon (PA).	
Ergonomy	Provides firm support when you are sitting, standing, or transferring to and from a toilet.	
	Good, broad support surface for the hand and arm.	



PRESSALIT.®

Product	VALUE support arm, fixed height	
Item number	R1100000	
Features	The support arm can fold up when not in use or to make more space.	
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.	
Cleaning	VALUE support arms. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use corrosive or abrasive cleaners as it may result in the surface being damaged. For surface disinfection, chlorine-based disinfectants may be used according to the product specification and safety precautions for these products. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% WipeClean UniversalCleaning Chrolorine Disinfection Wipes Klorilli (Kilito Clean) NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.	
Declaration of conformity	CE MDR This product is in compliance with all relevant requirements of: - Regulation (EU) 2017/745 on medical devices.	



PRESSALIT.

Product	
Item number	r

VALUE support arm, fixed height

R1100000


Installation in different wall types

Concrete >B25

V8593 - 4 countersunk screws Ø10 x 80, with white screw covers are included.

Plugs to be ordered separately.






Solid Brick >= Mz12

V8593 - 4 countersunk screws \emptyset 10 x 80, with white screw covers are included.

Plugs to be ordered separately.





Solid Sand Lime Brick >= Hlz12

V8593 - 4 countersunk screws Ø10 x 80, with white screw covers are included.

Plugs to be ordered separately.






Aerated Concrete P4

V8593 - 4 countersunk screws Ø10 x 80, with white screw covers are included.

Plugs to be ordered separately.





Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8593 - 4 countersunk screws Ø10 x 80, with white screw covers are included.

Plugs to be ordered separately.





PRESSALIT®

Product Item number	VALUE support arm, fixed height R1100000	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant	
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	

Bolts for wall fixing are included. It is the responsibility of the installer to ensure that suitable plugs are used. Please see mounting instruction.

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com

PRESSALIT.