

PRESSALIT.

Product	VALUE fold down grab bar with leg, fixed height		
Item number	R1101000		
	VVS:615722400		
	NRF:6191641		
	EAN:5708590176413		
	HMI: 25412		
	NBS:N13:436		
	DB: 2076621		
	FDA: ILS/D135866		
Color	White		
Product description	Fold down grab bar with leg, fixed, foldable, length 33.5", height 33.5". The ergonomic design gives a secure and comfortable grip as well as a good sense of where the support arm ends. Incl. fixing bolts for brick wall. Plugs depend on wall type and must be ordered separately. VALUE fold down grab bar with leg, fixed, foldable, length 33.5", height 33.5". The ergonomic design gives a secure and comfortable grip as well as a good sense of where the support arm ends. Materials: Rilsan-coated steel, pressure-cast aluminium, plastic. Incl. fixing bolts for brick wall. Plugs depend on wall type and must be ordered separately.		
Adjustability	Fixed mounting		
Product capacity	Maximum load: 300 lbs. When the fold down grab bar is loaded with 300 lbs, each mounting bolt is loaded with 180 lbs.		
Materials	asic material: Steel		
	Surface material: Rilsan		



PRESSALIT.®

Product	VALUE fold down grab bar with leg, fixed height
Item number	R1101000
Ergonomy	Provides firm support when you are sitting, standing, or transferring to and from a toilet.
	Good, broad support surface for the hand and arm. The rounded form gives a firm and comfortable grip.
Features	The grab bar can fold up when not in use or to make more space.
	With leg for extra support.
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.



PRESSALIT®

Product	VALUE fold down grab bar with leg, fixed height R1101000		
Item number			
Cleaning	This product should be cleaned with hot water or a mild cleaning solution.		
	Do not use corrosive or abrasive cleaners as it may result in the surface being damaged. For surface disinfection, chlorine-based disinfectants may be used according to the		
	product specification and safety precautions for these products.		
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.		
	DISINFECTANTS: Clinimax Difficil-S		
	Erisan OXY+		
	Sprit (husholdningssprit)		
	Suma Bac D10		
	Virkon Rodalon Desinfektionsspray		
	Lysoformin Spezial		
	CaviCide		
	Sufanios Premium		
	Tvättsprit 70% WipeClean UniversalCleaning		
	Chrolorine Disinfection Wipes		
	Klorilli (Kiilto Clean)		
	NON-DISINFECTANTS:		
	Suma Star free D1 Taski 100		
	Taski 200		
	Milizid Citro		
	The product must be wiped down with a soft rag wrung out in clear water immedia after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.		
Declaration of conformity	This product is in compliance with all relevant requirements of regulation (EU) 2017/745 on medical devices.		



PRESSALIT®

Product	VALUE fold down grab bar with leg, fixed height
Item number	R1101000

Mounting in different wall types

Mounting in different wall types				
	Concrete >B25 V8593 - 4 countersunk bolts Ø10 x 80, with white screw covers are included. Plugs to be ordered separately.			
	Solid Brick >= Mz12 V8593 - 4 countersunk bolts Ø10 x 80, with white screw covers are included. Plugs to be ordered separately.			
	Solid Sand Lime Brick >= HIz12 V8593 - 4 countersunk bolts Ø10 x 80, with white screw covers are included. Plugs to be ordered separately.			
	Aerated Concrete P4 V8593 - 4 countersunk bolts Ø10 x 80, with white screw covers are included. Plugs to be ordered separately.			
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8593 - 4 countersunk bolts Ø10 x 80, with white screw covers are included. Plugs to be ordered separately.			



PRESSALIT®

Product Item number	VALUE fold down grab bar with leg, fixed height R1101000	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant	
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	

Bolts for wall fixing are included. It is the responsibility of the installer to ensure that suitable plugs are used. Please see mounting instruction.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8789 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

PRESSALIT.