

## PRESSALIT.

T7304

T2405

A7202

A7050

Toilet seat Ergosit without cover, 50 mm raised With stabilising buffers and special hinges adapted to raised toilet seat.

Item number R19000

VVS:615690000 NRF:6190518

EAN:5708590082035

HMI: 12497 NBS:N13:300

Toilet seat, Ergosit, with stabilising buffers, w/o cover,


raised 50 mm. With raised cross bar hinge

Colour White

**Description** Toilet seat, Ergosit, with stabilising buffers, w/o cover,

raised 50 mm.

With raised cross bar hinge



Materials Seat: Thermoset plastic (urea)

0

Strap: Stainless steel V2A

Raiser: Nylon (PA)

Special buffer: ABS-plastic

Product capacity

This product has been tested statically up to 375 kg. As the European standard for technical aids for disabled, BS/EN 12182:2012, requires a static test with safety factor

1.5, the nominal maximum load for this product is therefore 250 kg.

Weight2,2 kgGross weight2,5 kgWeight per crate2,5 kgQty per crate1

Qty per pallet



## PRESSALIT.

Toilet seat Ergosit without cover, 50 mm raised With stabilising buffers and special hinges adapted to raised toilet seat.

Cleaning

Use a mild soap solution to clean the toilet seat. Please take care that the seat and hinges are not left damp. For disinfecting the seat, e.g. ethanol 85% can be used. Make sure that the product is wiped down with a soft rag wrung out in clear water and dried off with a soft, dry cloth immediately after disinfection.<br/>

| Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.<br/>
| Strict | Stric

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com