

-

## PRESSALIT.

## Toilet seat Dania with cover, 2" raised With stabilizing buffers and special hinges adapted to raised toilet seat.

ltem number	R33000 VVS:615685000 NRF:6190584 RSK:7972415 EAN:5708590070520 HMI: 1810 NBS:N13:300 DB: 2296029 Toilet seat, Dania, with stabilizing buffers, w/cover, raised 2". With raised cross bar hinge
Color	White
Description	Toilet seat, Dania, with stabilizing buffers, w/cover, raised 2". With raised cross bar hinge
	A7220 A8103 T7304 T7304 T72405 A7202 T9807 T9807 A7050 *85 mm
Materials	Seat/cover: Thermoset plastic (urea) Strap: Stainless steel V2A Raiser: Nylon (PA) Special buffer: ABS-plastic
Product capacity	This product has been tested statically up to 495 lbs. As the European standard for technical aids for disabled, EN 12182:2012, requires a static test with safety factor 1.5, the nominal maximum load for this product is therefore 330 lbs.
Weight	3,9 kg
Gross weight	4,2 kg
Weight per crate	4,2 kg
Qty per crate	1
Crates per pallet	60
Qty per pallet	60



## Toilet seat Dania with cover, 2" raised With stabilizing buffers and special hinges adapted to raised toilet seat.

Cleaning	Use a mild soap solution to clean the toilet seat. Please take care that the seat and hinges are not left damp. For disinfecting the seat, e.g. ethanol 85% can be used. Make sure that the product is wiped down with a soft rag wrung out in clear water and dried off with a soft, dry cloth immediately after disinfection. br> <i>Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.</i>
Warranty	Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.

## pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

