

PRESSALIT.

Toilet seat Dania with cover, 50 mm raised With stabilising buffers and special hinges adapted to raised toilet seat. Incl. splash guard.

Item number R43000

VVS:615697000 NRF:6191645

EAN:5708590186696

HMI: 88826 NBS:N13:300 DB: 2296032


Toilet seat, Dania, with stabilising buffers, w/cover, raised 50 mm, incl. splashguard. With raised cross bar


hinge


Colour White

Description Toilet seat, Dania, with stabilising buffers, w/cover,

raised 50 mm, incl. splashguard With raised cross bar hinge







Materials Seat/cover: Thermoset plastic (urea)

Strap: Stainless steel V2A

Raiser: Nylon (PA)

Special buffer: ABS-plastic

Product capacity

This product has been tested statically up to 225 kg. As the European standard for technical aids for disabled, BS/EN 12182:2012, requires a static test with safety factor

1.5, the nominal maximum load for this product is therefore 150 kg.

Weight 4,4 kg
Gross weight 4,7 kg

Weight per crate 4,7 kg

Qty per crate 1



PRESSALIT®

Toilet seat Dania with cover, 50 mm raised With stabilising buffers and special hinges adapted to raised toilet seat. Incl. splash guard.

Qty per pallet

0

Cleaning

Use a mild soap solution to clean the toilet seat. Please take care that the seat and hinges are not left damp. For disinfecting the seat, e.g. ethanol 85% can be used. Make sure that the product is wiped down with a soft rag wrung out in clear water and dried off with a soft, dry cloth immediately after disinfection.

| Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.

| Strict | Stri

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

PRESSALIT: