
PRESSALIT®

Product	Lift for wall cupboard, electrically height adjustable
Item number	RK1021
	EAN:5708590265759 HMI: 42888
Product description	The name INDIVO relates to the individual configuration of the products. Lift for wall cupboards, with 2 motors, height adjustable down/out, with switches. Lengths from 1201 - 2400 mm. Height adjustable 430 mm. Incl. mounting kit for brick wall Please state desired length when ordering
Adjustability	Height adjustable
Adjustment height	430 mm
Product capacity	Max. load (including cupboards): 2 lifts: 220 kg
Speed upwards	Speed up mm: 18 mm/s Speed down mm: 18 mm/s
Noise level	48 dB
Materials	Material: Lift motor: Steel Cross braces: Aluminium Switches: ABS plastic
Ergonomy	Wall cupboards are moved diagonally, that is both vertically and towards the user. This makes it easy for seated users and children to see and access covered contents. Height-adjustable wall cupboards provide extra storage options in kitchens where cupboards cannot be installed under worktops out of consideration for seated users.



Product	Lift for wall cupboard, electrically height adjustable
Item number	RK1021
Features	Lift heights for wall cupboards are adjusted via switches in the front worktop edge. Operating switches can be placed wherever you want along the front edge. The switches are colour-coded - aluminium to operate worktops, and red to operate wall cupboards. The design of the lifts ensures that the lift motors are as discreet as possible, regardless of the cupboard position. When the wall cupboards are lowered 430 mm to their lowest position, they are also extended 180 mm towards the user.
Actuator (motor)	LA31 Deskline (Linak), 3500N, IPX1
Control box	CBD6 (Linak)
Wired remote control	HB53 (Linak), IPX1
Power consumption (maximum load)	Power consumption by maximum load, watt: 187 W Power consumption by standby: 1,5 W
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.

Product	Lift for wall cupboard, electrically height adjustable
Item number	RK1021

Cleaning

INDIVO lift for kitchenwall cupboard.
The product is to be cleaned with hot water or a mild soapy cleaning agent.
Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.

The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.

DISINFECTANTS:
Clinimax Difficil-S
Erisan OXY+

NON-DISINFECTANTS:
Suma Star free D1
Taski 100
Taski 200

The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.

DECALCIFICATION OF ALUMINUM PARTS:
Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts must be wiped over with a damp cloth wrung out in clear water.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com