




# PRESSALIT®

<b>Product</b> <b>Item number</b>	Lift for worktop, electrically height adjustable RK1083
<b>Product description</b>	<p> EAN: 5708590293790  HMI: 61268 </p>  <p> The name INDIVO relates to the individual configuration of the products. </p> <p> Electric lift for freestanding worktop.  For worktops from 2401 - 3000 mm.  Height adjustable 300 mm.  Including 2 telescopic legs, brackets, longitudinal and cross braces and switch.  Pressalit recommends overhang of 400 mm at either end of worktop to allow for ease of approach in wheel-chair.  Please state desired length when ordering. </p>
<b>Adjustability</b> <b>Adjustment height</b> <b>Product capacity</b> <b>Speed upwards</b> <b>Noise level</b>	<p> Height adjustable  300 mm </p> <p> Maximum load (evenly distributed):  100 kg including worktop. </p> <p> Speed up mm: 20 mm/s  Speed down mm: 20 mm/s </p> <p> 45 dB </p>
<b>Materials</b>	<p> Material:  Telescopic leg: Aluminium, ABS plastic  Cross braces: Aluminium  Brackets: Steel  Cable tray: ABS plastic  Switches: ABS plastic  Surface treatment:  Brackets: Powder lacquered (grey RAL 9006) </p>



<b>Product</b>	Lift for worktop, electrically height adjustable
<b>Item number</b>	RK1083
<b>Ergonomy</b>	<p>A freestanding electric Indivo solution is a flexible work or dining table, primarily intended for use in the kitchen.</p> <p>The height of the worktop can be quickly and easily adjusted to the given user or situation.</p> <p>A freestanding worktop can also be used in rooms in which the walls are not strong enough to support the wall-mounted models.</p>
<b>Features</b>	<p>Lift heights are adjusted via switches set in the edge or directly under the worktop. Operating switches can be placed anywhere.</p> <p>The design of the legs and feet make the table stable and secure, and ensure the lift causes minimal inconvenience to wheelchair users.</p> <p>The design of the lift makes it possible to use the worktop from all sides.</p> <p>Height adjustable over a range of 300 mm.</p> <p>Available for worktops of any length between 1400 mm and 3000 mm.</p>
<b>Actuator (motor)</b>	DB4 Deskline (Linak) 1000 N, IP22
<b>Control box</b>	CBD6 (Linak)
<b>Power consumption (maximum load)</b>	<p>Power consumption by maximum load, watt: 300 W</p> <p>Power consumption by standby: 2 W</p>
<b>Warranty</b>	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.



<b>Product</b>	Lift for worktop, electrically height adjustable
<b>Item number</b>	RK1083
<b>Cleaning</b>	<p>INDIVO lift for kitchen worktop. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.</p> <p>The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.</p> <p><b>DISINFECTANTS:</b> Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70%</p> <p><b>NON-DISINFECTANTS:</b> Suma Star free D1 Taski 100 Taski 200 Milizid Citro</p> <p>The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.</p> <p><b>DECALCIFICATION OF ALUMINUM PARTS:</b> Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts must be wiped over with a damp cloth wrung out in clear water.</p>



# PRESSALIT®

<b>Product</b>	Lift for worktop, electrically height adjustable
<b>Item number</b>	RK1083

---

[pressalit.com](http://pressalit.com)

---

Pressalit A/S  
Pressalitvej 1  
DK-8680 Ry  
Tel.: +45 8788 8788  
Fax: +45 8788 8789  
E-mail: [pressalit@pressalit.com](mailto:pressalit@pressalit.com)

# PRESSALIT®