
PRESSALIT®

Product	PLUS handrail section 608 mm, incl. wall rosette
Item number	RT321000
	VVS:777569210 NRF:6311254 EAN:5708590146539 NBS:N13:436
Colour	White



Product description

PLUS hand rail tube, with wall rosette and connecting unit female joint.
Length 608 mm, diameter 33 mm.
Requires other hand rail elements for installation.
Please enquire for special hand rail solutions.
Please note that RT360 PLUS hand rail wall mounting with strap must always be installed at all joints of tubes or every 1200 mm.
Excl. mounting kit.
See Technical datasheet (pdf) for information on fixings suitable for various wall types.

PLUS hand rail tube, with wall rosette and connecting unit female joint.
Length 608 mm, diameter 33 mm.
Requires other hand rail elements for installation.
Please enquire for special hand rail solutions.
Please note that RT360 PLUS hand rail wall mounting with strap must always be installed at all joints of tubes or every 1200 mm.
Materials: Powder-coated aluminium and plastics.
Excl. mounting kit.

Product capacity

Maximum load: With a span up to 1000 mm: 210 kg
With a span up to 1300 mm: 150 kg.

Materials

Basic material: Aluminium

Surface material: Polyester lacquer

Cover cap: Cycoloy plastic

Ergonomy


The 33 mm diameter enables the rail to be held comfortably and firmly. The projection of 50 mm from the wall makes it easy to take hold of the rail.

Product	PLUS handrail section 608 mm, incl. wall rosette
Item number	RT321000
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.
Cleaning	The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based or corrosive cleaners as it may result in the surface being damaged.

PRESSALIT®


Product	PLUS handrail section 608 mm, incl. wall rosette
Item number	RT321000


Installation in different wall types



Concrete >B25


V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.






Solid Brick >= Mz12


V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.






Solid Sand Lime Brick >= Hlz12


V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.






Aerated Concrete P4


V8665 - Mounting kit, 4 bolts M5 x 50 - plugs FTP K 6.
To be ordered separately.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8. NB!
Plugs are not needed.
To be ordered separately.





Product	PLUS handrail section 608 mm, incl. wall rosette
Item number	RT321000



Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood


Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)

Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.





Drywall (2 x 12,5 mm) water-resistant

Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.



Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com