

PRESSALIT.

Product Item number	PLUS handrail section 652 mm, incl. wall rosette and strap RT331035	
	VVS:777569315	
	EAN:5708590146621	
	NBS: N13:436 RT330 - A = 366 RT331 - A = 662 RT332 - A = 790 RT333 - A = 1090	
Colour	Red (RAL 3003)	
Product description	PLUS hand rail tube, with wall rosette and strop. Length 652 mm, diameter 33 mm. Requires other hand rail elements for installation. Please enquire for special hand rail solutions. Excl. mounting kit. See Technical datasheet (pdf) for information on fixings suitable for various wall types.	
	PLUS hand rail tube, with wall rosette and strop. Length 652 mm, diameter 33 mm. Requires other hand rail elements for installation. Please enquire for special hand rail solutions. Materials: Powder-coated aluminium and plastics. Excl. mounting kit.	
Product capacity	Maximum load: With a span up to 1000 mm: 210 kg With a span up to 1300 mm: 150 kg.	
Materials	Basic material: Aluminium	
	Surface material: Polyester lacquer	
	Cover cap: Cycoloy plastic	
	Strap: Nylon (PA)	
Ergonomy	The 33 mm diameter enables the rail to be held comfortably and firmly. The projection of 50 mm from the wall makes it easy to take hold of the rail.	
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.	



PRESSALIT.

Product Item number	PLUS handrail section 652 mm, incl. wall rosette and strap RT331035
Cleaning	The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based or corrosive cleaners as it may result in the surface being damaged.



PRESSALIT.

Product Item number	PLUS handrail section 652 mm, incl. wall rosette and strap RT331035			
Installation in different wall types				
	Concrete >B25 V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.			
	Solid Brick >= Mz12 V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.			
	Solid Sand Lime Brick >= Hlz12 V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.			
	Aerated Concrete P4 V8665 - Mounting kit, 4 bolts M5 x 50 - plugs FTP K 6. To be ordered separately.			
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8. NB! Plugs are not needed. To be ordered separately.			



PRESSALIT®

Product Item number	PLUS handrail section 652 mm, incl. wall rosette and RT331035	d strap
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	<u>^!</u>

pressalit.com